WILLIAM ALLEY CIVIL ENGINEER

ODESSA, TEXAS

July 7th, 1930

Hon. J. H. Walker, Commissioner Austin, Texas.

Dear Sir:-

Preliminary to making a survey of several sections in Block B-15, Block B-14, Block B-8 and Block 45, Tp. 2 S., all in Ector County, I made retracements as follows.

I, run a line through Block B-15 from the SE corner of Block 45, Tp. 2 S. and the SW corner of Block 44, Tp,2 S. to the corner of secs. 20 and 21 Block B-15 and secs. 11 and 20 of Block B-14 and found the correct course of same to be, as determined by Polaris observation, S.74°24'W. and the total distance through the Block to be 11631.3 Varas, I made this line a base line for the surveys of this Block.

From a large stone and plunger coupling at the SE corner of Block B-14 and the SW corner of Block B-15, I run a line along the W. bdy. of Block B-15 and the E. bdy. of Block B-14, to the NE corner of Block B-14 and the SE corner of Block B-8, and found the true course of said line to be N.15°19'W. and the total distance to be 10447.3 Varas. I found no original corners between the Block corners. I, retraced the E. bdy. of Block B-8 to the corner of secs. 1 and 2 Block B-15 and secs. 10 and 11 Block B-8, I found all the corners on this line, established at time the patent surveys were made of the secs., in Block B-8, along this line. The true course of this line is N.15°19'W. and the distances are as shown in the patent notes.

From the corner of secs. 17, 18, 23 and 24, in Block B-15

WILLIAM ALLEY CIVIL ENGINEER

Page 2

ODESSA, TEXAS

as determined by me, I run a line between secs. 17 and 18, 13 amd 14, and 7 and 8 and tied to the original point, 95.0 Varas S.74°22'W. from the old original corner of secs. 23 and 24, Block 45, Tp. 2 S. which is a mound of stone, making this line a guide line for the surveys in Block B-15, The course of this guide line is N.15°18'W.

From the SE corner of Block 45, Tp. 2 S. and the SW corner of Block 44, Tp. 3 S. which is a plunger coupling and mound of stone. I run a line along the E. bdy of Block 45, Tp. 2 S. and the W. bdy. of Block 44, Tp. 2 S. at 11415.0 Varas to a plunger coupling and mound of stone the corner of secs. 11 and 12 Block 45, Tp. 2 S. and 7 and 18 Block 44, Tp. 2 S. the true course of seid line is N.15°37'W., no original corners were found on this line. I continue my line and at 15220.0 Varas found the old original corner of Blocks 44 and 45, Tps. 1 S. and 2 S., the true course of this line is N.15°37'W.

From the SE corner of Block 45, Tp. 2 S. and corner of Block B-15, I retraced the NE bdy. of Block B-15, I located some of the original corners on this line a descreption of same and courses and distances are shown in the field notes of the secs., adjoining this line in Block B-15 and Block 45, Tp. 2 S.

From the NE corner of Block B-14 and the SE corner of Block B-8, which is a 1½ in. iron pipe marked NE 1 B-8 NW 10 B-15. I retraced the N. bdy. of Block B-14, and the S. bdy. of Block B-8 and found the total length of this line to be 9555.2 Varas and its true course S.74°52'W. From the cor. of Blocks B-8, B-9, B-14, B-18

WILLIAM ALLEY CIVIL ENGINEER ODESSA, TEXAS

Page 3

which is a 2 inch iron pipe, marked SW 25 B 8, NW 5 B 14, I retraced the west boundary of sections 5 and 6 of Block B-14. I found the course of this line to be S.15°19'E. and the length 3801.5 Varas.

Yours truly

William aley

Filed July 19th 1930

See Sketch filed 7/19/30

Go2

Counter 21671

I form d the occurred of this line to be al. 1501818. And the Keep With Ector County Rolled Sk. "WA Report By William Alley Filed 7-19-30 Counter 21642