

LW  
OK

To Hon. J. T. Robison, Commissioner of the  
General Land Office of the State of Texas.

Report of Survey made in locating the exterior  
lines of part of Block 2, W. C. R. R. Co. and  
the North line of Block 4T, T. & N. O. R. R. Co.  
situated in Hansford County, Texas, affecting S  
Surveys 12- 13- 14- 19- 20- 21- 24- and 25 in  
said Block 2 and affecting Surveys 4- 5- 6- 7-  
8- 9- 28- 32- 34 and 36 in said Block 4T.

Beginning at the identified South east corner of Survey 69, Blk. 45,  
a stone set marked "SE 69" same being North west corner of Survey  
12, and NE corner of Survey 13, Block 2.

Thence S  $89^{\circ} 47'$  W along South line of said Survey 69, North  
line of said Survey 13, 1942 varas old 4 pit corner the SW corner  
of Survey 69 and SE corner of Survey 70, Block 45, H. & T. C. Ry. Co.  
Grant and NW corner of Survey 13 and NE corner of Survey 14, Block 2  
at 3819 varas cross draw called for in Corrected Field Notes on  
Survey 70, Block 45, 3942 varas stone set and rock mound the SW cor-  
ner of Survey 70, set by Joe L. Long, as called for in Corrected  
Field Notes covering Survey 70, same being the NW corner of  
Survey 14, Block 2.

Thence S  $00^{\circ} 08'$  E at 1902 varas pass rock mound, at 3785  
pass iron pipe set by James, County Surveyor of Hansford County,  
for NW corner of Survey 26, and SE corner of Survey 19, Block 2,  
5685 varas find pipe set by James for SW corner 26, Block 2,  
in North line of Block 4T.

Thence S  $89^{\circ} 48'$  W at 1950 varas pass 4 pit corner at 1996.2  
varas set lath for temporary NW corner of Survey 6, Block 4T, at  
3910 varas fall  $4\frac{1}{2}$  vrs South of old 4 pit corner under fence, the  
SW corner of Survey 28, Block 2.

Thence N  $00^{\circ} 24'$  W, 1900 varas to old stone mound called for  
by Joe L. Long, the SE corner of Survey 89, Block 45, and NE corner  
of Survey 1, Block 4T.

Returning to the SW corner of Survey 26, Block 2.

Thence East along the South line of said Survey 26, at 449 varas  
cross draw. 2000 varas to sucker-rod iron set by James, the SE cor-  
ner of Survey 26, and SW corner of Survey 25, Block 2.

Thence N  $89^{\circ} 47'$  E along South line of Survey 25, at 1805.5  
pass dimly marked 3 pit corner the NE corner 8, and NW corner 9,  
Block 4T, 1942 car axle set by James, the SW corner 24, and SE  
corner 25, Block 2.

52

Thence N 89° 42' E at 1666.9 varas pass fence corner the NW corner of Survey 10, and NE corner of Survey 9, Block 4T, 1943.4 varas to pipe and 4 pits set under fence by James, the SE corner of Survey 24 and SW corner of Survey 23, Block 2.

Thence N 00° 10' W at 1898 varas a 2 inch pipe and 4 pits, by James, the SW corner of Survey 22, and NE corner of Survey 24, (the NW corner 24, a 1 inch shaft and 4 pits by James, bears S. 89° 24' W, 1943.4) at 3896 varas 1 inch pipe marked "SW 11" and 4 pits by James, the SW corner of Survey 11 and NE corner of Survey 21, (the NW corner 21 bears S 88° 58' W, 1943.4 varas, a shaft and 4 pits by T. O. James).

From NE corner 21;  
Thence N 00° 6' W 1906 varas to 3/4 inch pipe marked "NW 11" and 4 pits by Rupert C. Allen the NW corner Survey 11 and NE corner of Survey 12.

Thence S 89° 00' W 1943.2 varas along North line of Survey 12, to the place of beginning.

- - - - -

Block 4T

The North line Block 4T having been determined on ground we then go to the SW corner of Survey No. 32, Block 4T, a 3/4 inch pipe set in old 4 pit corner by Joe L. Long, State Land Surveyor.

Thence West at 654 varas cross draw called for by Long, at 1344 varas cross horse canon called for by Long, 1900 varas pipe and 4 pits by H. E. James set for the SW corner of Survey 33, same being SE corner of 34 and NE corner of Survey 36.

Thence North 1900.8 varas pipe and 4 pits by James set for the NW corner of Survey 33, same being NE corner of Survey 34, and SW corner of Survey 4, in said Block 4T (old stone mound and iron rod under North and South fence bears West 1913.8 varas).

From NE corner of 34:  
Thence N 00° 24' W at 1900 varas find no corner at 3800 varas and old stone mound from which draw bears East as called for by Joe L. Long, State Surveyor.

Returning to SE corner of Survey 34, and NE corner 36, said Block 4T.

Thence West 1913.8 varas to pipe in old 4 pit corner the SE corner of Survey 116, Block 45 from which old stone mound and iron rod, the NE corner of said Section 116, and NW corner Survey 34, Block 4T bears North 1900.8 varas.

Thence S 00° 05' E 1905 varas we find pipe and 4 pits the SE corner of Survey 35 and SW corner of Survey 36, Block 4T.

Thence East 1911 varas to sucker rod iron pipe and 4 pits by James, the SE corner of Survey 36.

S'

Counter 24955

SR

Returning to the SW corner Survey 32.

Thence East at 304 varas cross draw as called for by Joe L. Long, State Surveyor, 1903 varas we find a pipe set in old 4 pit corner.

Thence North  $89^{\circ} 51' E$  1904.5 varas bolt set in old 4 pit corner.

Thence  $S89^{\circ} 55' E$  at 870 varas old road called for by long, 1904 varas pipe and 4 pit corner by James from which corner bears due South one mile.

Thence East 1891.5 varas to pipe in old 4 pit corner the SW corner of Survey 28 and SE corner of Survey 29.

Thence East 1904.4 varas we find pipe marked "NE 42" set in old 4 pit corner from which the South West corner of Section 26, bears East one mile.


Thence North 1911.8 varas to pipe set in center of road grade the NE corner of Survey 28, and SE corner of 9, and SW corner of Survey 10, this Block as set by James in establishing public road, continuing course North beginning new measurement at 1903.8 varas to point at fence corner in South line of Survey 24, Block 2, for NE corner 9, and NW corner 10, Block 4T, from which the SE corner 24, Block 2 bears  $N 89^{\circ} 42' E$  276.5 varas; SW corner 24 and SE corner 25, Block 2 bears  $S 89^{\circ} 42' W$  1666.9 varas.

The NW corner of Survey 28, NE 29, SE 8 and SW 9, an axle one inch by one inch and 4 pits we found set by James, SW corner of 8, and SW corner of 7, set by Dressin in surveying Section 30. NW corner of 32, SE corner of 4, SW 5, and NE corner of 33, a pipe and 4 pits at fence corner we found as set by James in surveying Section 33.


After determining course and distance between all corners found of the ground, as above mentioned, we proceeded to set all other corners to conform thereto affecting Sections 12- 13- 14- 19- 20- 21- 24 and 25, Block 2 and Sections 4-5-6-7-8-9-28-32-34 and 36 in Block 4T, more fully described in plat herewith filed and field notes covering said Sections.

Dated this 18th day of November 1926.

Respectfully submitted,

  
Rupert C. Allen  
Licensed State Land Surveyor

Filed in Hansford County, Texas, this 18th day of November 1926.  
Recorded in Vol. 2, page 118-119 & 120 Surveyor Records of said County.

  
Rupert C. Allen  
Licensed State Land Surveyor

File No. 6

Harford County

Rupert's Connection

~~Field Notes~~  
Dated Nov. 18, 1926.

Filed Jan 6 1927

J. T. Robison Com'r.

W. H. McDonald  
File Clerk

Repert Allen's Report on Con-  
nections & Corrections of Block  
lines of WCRRC Co BIK 2, & T &  
NORy Co., BIK 4T,  
Dated Nov. 18, 1926.  
Filed Jan. 6. 1927.

Counter 24957