

D-425  
28615  
RECEIVED  
MAR 16 1953  
GENERAL LAND OFFICE

Surveyor's Report

S 1/2 Survey No. 810, B. F. I. & M. Co.  
Sur. No. 815, John H. Gibson  
Sur. No. 817, John H. Gibson  
Sur. No. 819, John H. Gibson  
S 1/2 Sur. No. 820, John H. Gibson  
NW 1/4 Sur. No. 820, John H. Gibson  
S.W. 1/4 Sur. No. 820, John H. Gibson

Situated in Kendall County, Texas

I started at an old stone md. in the East line of Survey No. 227, H.E. & W. T. R.R. Co. and in the West line of original survey No. 810, for the N. W. corner of the S 1/2 Survey No. 810 and the S.W. corner of the N 1/2 Survey No. 810, from which a L.O. new 24" dia. brs. S. 17° W. 158.0 varas, a L.O. new 30" dia. brs. S. 17° 30' W. 148.0 varas, both marked X; Thence I ran S. 88° 58' E. 1921.3 varas to an old stone mound situated 1.0 vara South of a fence on the West slope of a ravine, being the S.W. corner of Survey No. 816, the N.W. corner of Survey No. 815, the N. E. corner of the S 1/2 Sur. No. 810 and the S.E. corner of the N 1/2 of Survey No. 810 and from said stone md. a L.O. stump brs. N. 27° E. 31 varas.

Thence I ran N. 89° 41' E. 2290.0 varas to an old stone mound situated 2.0 varas North of a fence corner, for the S.E. corner of Survey No. 816 the S.W. corner of original Survey No. 818, the N.W. corner of Survey No. 817, and the N. E. corner of Sur. No. 815, and from said stone md. a Sp. Oak clump brs. N. 35° E. 18.0 varas and from said stone md. I found a large rock which was marked X brs. S. 50° 45' W. 9.1 varas. From said stone mound I ran with a fence line N. 0° 15' W. 2052.8 varas to a fence corner taken as the N. W. corner of original Survey No. 818; From stone mound for the N. E. corner of Sur. No. 815, I ran with a general course of a fence, N. 89° 45' E. at 1009.5 varas an old st. md. at fence corner for the S.W. corner of the S.E. 1/4 of Sur. No. 818 and the S.S.E. corner of the NW 3/4 Sur. No. 818, from said stone mound a L.O. new 14" dia. brs. N. 31° E. 19.3 varas, a L.O. new 10" dia. brs. N. 15° 30' E. 18.7 varas, both marked X, 2020.7 varas in all to an old st. md. at fence corner for the N.E. cor. of Sur. No. 817, the N.W. cor. of Sur. No. 819, the S.W. cor. of original Sur. No. 820, and the S.E. corner of original Survey No. 818, from which I marked a L.O. 5" dia. brs. S. 65° E. 34.8 varas, marked X.

Thence I ran with the general course of a fence, N.  $0^{\circ} 45'$  W. at 1052.8 varas an old st. md. situated 2.0 varas South of a fence corner, for the N.E. cor. of the S.E. 1/4 of Sur. No. 818, the E.S.E. cor. of the NW 3/4 of Sur. 818, the N.W. cor. of the S.W. 1/4 Sur. No. 820, the S.W. cor. of the N.W. 1/4 Sur. 820, from which a L.O. new 8" dia. brs. N.  $30^{\circ}$  W. 12.6 varas, marked X, 2066.2 varas an old st. md. at fence corner for the N.W. corner of original Survey No. 820 and the N. E. corner of original Survey No. 818, being in the South line of Sur. No. 35, H. & O. B. R. R. Co., from which a P.O. stump brs. S.  $6^{\circ}$  E. 13.0 varas, I marked a L.O. 8" dia. brs. S.  $18^{\circ}$  E. 4.8 varas, marked X.

Thence I ran with the general course of a fence, N.  $89^{\circ} 37'$  E. 1428.8 varas to an old stone mound at fence corner for the S.E. cor. of Sur. No. 35 and the W.S.W. corner of Sur. No. 347, from which a P.O. new 20" dia. brs. S.  $9^{\circ}$  W. 88.8 varas, a L.O. new 16" dia. brs. N.  $38^{\circ}$  W. 35.0 varas, both marked X;

Thence I ran with the general course of a fence, N.  $1^{\circ} 39'$  E. 1128.5 varas to an old stone mound at fence corner for the N.W. corner of Survey No. 347;

Thence I ran with the general course of a fence, N.  $89^{\circ} 39'$  E. 730.1 varas to an old st. md. at fence corner, for the N. E. corner of Sur. No. 347, from which a P.O. new 22" dia. brs. S.  $4^{\circ}$  W. 23.0 varas, marked X; From stone mound at fence corner post for the S.E. corner of Survey No. 35 and the W.S.W. corner of Sur. No. 347, I ran N.  $89^{\circ} 37'$  E. 630.8 varas and set a 3/4" dia. x 3' pipe in the center of an old stone mound for the N. E. corner of original Survey No. 820 which is a reentrant corner of Survey No. 347;

Thence I ran S.  $0^{\circ} 40'$  E. at 1498.6 varas found an old stone mound for the S.S.W. corner of Survey No. 347 being the N. W. corner of original Survey No. 56, from which a B. J. Stump brs. East 5.0 varas, and from this mound I ran East 60.0 varas and found another stone mound situated 6.8 varas West of a fence corner for the S.S.E. corner of Sur. No. 347 and the S.W. corner of Sur. No. 840;

From the old stone mound for the S.W. corner of Sur. No. 840, I ran N.  $89^{\circ} 24'$  E. 928.3 varas to an old st. md. at fence corner post for the N. E. corner of the N 1/2 of Survey No. 56, from which a L.O. stump brs. N.  $42^{\circ}$  E. 8.0 varas, a L.O. stump brs. N.  $44^{\circ} 30'$  E. 11.0 varas, both L.O.'s had been bulldozed out, I marked a B. J. 14" dia. brs.

S.  $78^{\circ} 15'$  W. 38.0 varas, marked X

From the old stone mound for the N. W. corner of the N 1/2 Sur. No. 56, I ran S.  $0^{\circ} 40'$  E. 564.0 varas and found an old stone mound on the top of a ridge for the N. E. corner of Sur. No. 819 and the S. E. corner of original Sur. No. 820, from which a L.O. new 12" dia. brs. S.  $65^{\circ} 15' W.$  32.0 varas, marked X J, a L.O. new 8" dia. brs. S.  $21^{\circ} W.$  18.0 varas, marked X;

Thence I ran S.  $89^{\circ} 31'$  W. 2056.6 varas to the old st. md. at fence corner for the N. W. corner of Sur. No. 819;

From the N. W. corner of the S.W. 1/4 Sur. No. 820 and the S. W. corner of the N.W. 1/4 Sur. No. 820, I ran N.  $89^{\circ} 34'$  E. 1029.2 varas and set a stone md. for the S.E. corner of the NW 1/4 Sur. No. 820 and the N. E. corner of the S.W. 1/4 Sur. No. 820, and marked two trees, a L.O. 14" dia. brs. N.  $40^{\circ} W.$  25.2 varas, a L.O. 6" dia. brs. N.  $58^{\circ} W.$  9.5 varas, both marked X ;

Thence I ran N.  $0^{\circ} 43'$  E. 1012.4 varas and set a 3/4" dia. x 3' pipe in the center of a stone mound for the N. E. corner of the N.W. 1/4 Sur. No. 820 and the N. W. corner of the E 1/2 Sur. No. 820;

From the stone mound I had set for the N. E. corner of the S.W. 1/4 of Sur. No. 820 and the S. E. corner of the N.W. 1/4 of Sur. No. 820, I ran S.  $0^{\circ} 43'$  E. 1052.0 varas and set a stone mound in the North line of Sur. No. 819 for the S.E. corner of the S.W. 1/4 of Sur. No. 820 and the S.W. corner of the E 1/2 of Sur. No. 820, and marked a L.O. 6" dia. brs. N.  $34^{\circ} 30' W.$  23.6 varas, marked X :

From the N. E. corner of Sur. No. 819 and the S.E. corner of original Sur. No. 820, I ran S.  $0^{\circ} 58'$  W. 1247.2 varas to an old st. md. at fence corner for the S. W. corner of the N 1/2 Sur. No. 56, from which a L.O. new 22" dia. brs. N.  $51^{\circ} 15' W.$  171.6 varas, marked X

Thence I ran N.  $89^{\circ} 38'$  E. 1013.5 varas to an old stone mound for the S. E. corner of the N 1/2 Sur. No. 56, from which a L.O. new 16" dia. brs. N.  $16^{\circ} 45' W.$  36.0 varas, marked X, a L.O. stump brs. N.  $4^{\circ} E.$  42.0 varas, the L.O. had been bulldozed out recently.

From the stone md. for the S.W. corner of the N 1/2 of Sur. No. 56, I ran S.  $0^{\circ} 58'$  W. 860.4 varas to an old st. md. situated 5.6 varas West and 2.1 varas South of a fence corner for the S. E. corner of Sur. No. 819, from which a Sp. Oak clump brs. N.  $23^{\circ} W.$  41.0 varas, I marked a double Cherry tree, the East fork 6" dia. brs. N.  $37^{\circ} 30' W.$  14.0 varas,

the West fork 8" dia. brs. N.  $38^{\circ} 50'$  W. 15.0 varas, both marked X

Thence I ran with the general course of a fence, N.  $89^{\circ} 15'$  W. at 2003.8 varas a fence corner post for the N. E. corner of Survey No. 152 1/2, and the N. W. corner of Survey No. 813, and from said fence corner post a L.O. new 14" dia. brs. West 138.0 varas, marked X ; 2008.6 vs.

Thence I ran South with the general course of a fence and found an old st. md. 6.0 varas West of a fence corner for the S.W. Cor. of Sur. No. 813;

Thence I ran East with the general course of a fence, 1900.1 varas to an old stone mound in fence line which probably is the S. E. corner of Sur. No. 813;

Thence I ran South with the general course of a fence, 184.0 varas to a point in a spring branch for fence intersection, from which a L.O. new 24" dia. brs. N.  $36^{\circ}$  W. 90.0 varas, marked X for the S.W. corner of Survey No. 1087, Chas. Oelkers.

From the N. W. corner of Sur. No. 813, I ran with the general course of a fence S.  $89^{\circ} 39'$  W. 4324.5 varas to an old st. md. at fence corner post for the N. W. corner of Survey No. 152 1/2 and the S. W. Cor. of Sur. No. 815, being in the East line of Sur. No. 809, from which a L.O. new 18" dia. brs. S.  $55^{\circ}$  W. 58.0 varas marked X ; We spent two days looking for the S. E. corner of Sur. No. 817 and the S. E. corner of Sur. No. 815, but all evidence points to the fact that these corners had been destroyed and the bearing trees removed. Mr. Willie Whitworth, one of the owners, said that his father had shown him these corners a few years previously, but said that they must have been destroyed within the last three years. We gave the South line of Survey No. 815 the distance corresponding to its North line and also gave the South line of Survey No. 817 the distance corresponding to its North line, setting 3/4" dia. x 3' pipes and marking bearing trees at each corner.

From the S.W. corner of Sur. No. 815, I ran with the general course of a fence, N.  $0^{\circ} 06'$  W. 924.8 varas to an old st. md. at fence corner post for the N. E. cor. of Sur. No. 809 and the S. E. corner of original survey No. 810, from which a L.O. stump brs. N.  $5^{\circ}$  E. 42.0 varas, I marked a L.O. 4" dia. brs. N.  $0^{\circ} 47'$  E. 4.1 varas, marked X:

Thence I ran with the general course of a fence, S.  $89^{\circ} 56'$  W. 1922.0 varas to an old stone md. at fence corner post, for the N. W. Corner of

Sur. No. 809 and the S.W. corner of original Survey No. 810, being in the East line of Survey No. 228, from which a L.O. stump brs. N.  $87^{\circ}$  E. 11.0 varas, I marked a L.O. 4" dia. brs. N.  $62^{\circ}$  E. 12.8 varas, marked X.  
Thence I ran with the general course of a fence, N.  $0^{\circ} 03'$  W. at 657.5 varas an old st. md. 1.0 vara East of a fence line for the N. E. Cor. of Sur. No. 228 and the S.E. corner of Sur. No. 227, 1180.6 varas in all to the place of beginning.

From the stone md. for the N. E. corner of Sur. No. 228 and the S.E. cor. of Sur. No. 227, I ran with the general course of a fence, S.  $89^{\circ} 48'$  W. 1795.7 varas to an old st. md. at fence corner for the N. W. cor. of Sur. No. 228 and the S.W. corner of Sur. No. 227, from which a L.O. new 18" dia. brs. N.  $54^{\circ}$  W. 62.0 varas, a L.O. new 12" dia. brs. N.  $80^{\circ}$  W. 20.0 varas, both marked X.

B. L. Enderle

B. L. Enderle  
Licensed State Land Surveyor



File No. 28

KENDALL County

## Sketch File

Filed March 16 1953

BASCOM GILES Com'r

W. H. Morris

Report to  
accompany  
Rolled Sk. 6  
By B.L.Enderle  
Feb. 21, 1953