The State of Texas County of Borden County Court in Vacation June 2nd, 1908.

On this day came on to be heard the "Survey" made by W. S. McClung, establishing the South East Corner of said Borden County. Also the survey made by W. S. McClung of the South boundary line of said Borden County.

Said W. S. McClung having been authorized to make said survey, and said survey having been examined by the Court and it appearing to the Court that said Survey is a correct and was truly made.

It is therefore ordered by the Court that the same be entered on the Minutes of the Court. The State of Texas

And Howard) Field Notes of a Survey of a connecting line and standard parallel made for Borden and Howard Counties by virtue of an order of the County court of Borden County, passed at the regular February term of said Court on the lith day of February 1908, and an o order of the County Court of Howard County passed at the regular term of said Court on the 29th day of February, 1908, concuring with the said County Court of Borden County for the purpose of establishing the South of boundary line said Borden County, and North boundary line of said Howard County.

We the undersigned surveyors met as directed by the order of said courts on the 30th day of March, 1908, at the South West corner of Jones County, same being the North West Corner of Taylor County.

S aid corner is a large stone marked S L J C W 30 S W C situated in the head of a small ravine 1060 varas 5.75 W and 55 varas N.144 W. from the S. E. corner of Survey No. 283 in the name of Robt.Spears as established by the T. & P. Ry. Co.

We identified said South West Corner of Jones County and began by sitting a stake with tack in top 2.13 feet South of said corner and by observation on polaris determined and established a true Meridian, by the Meridian thus established magnetic declination 10° 58' E.

(March 31st, 1908, we turn angle from the Meridian thus established to the IST. (secant N.89 58'20"W. and proceed with line on secant at 1901 varas set (hub in form on secant at its intersecting with standard parallel. (Continuing line on secant N.89 58'50"W. passing through farm and grove of

2ND. (mesqt. 1901 varas set a stke 1.27 feet South of secant on standard par-(allel in yard of farm house.

3RD. (Continuing line on secant N. 89 59'30 W. passing over point of rocky (hill 1901 varas set a stake 1.70 feet South of secant on standard parallel. 4TH. (Continuing line on secant West descending hill 1901 varas set a stake in (Valley 1.27 feet South of secant on parallel. The State of Texas I County of Borden

I Rodway Keen, Clerk of the County Court of Borden County Texas do her by certify that the above and foregoing instrument of writing is a true and correct copy of the original as the same appears of record in my office in the Minutes of the Cunty Court Volume 1, at page 140 to 150 respectively.

Given under my hand and seal of Office this 23rd day of June A.D. 1908.

8 Borden County Fourt of Borden County Texas.

N

Ł

.

m9

237 varas(the stone being removed by some one) A mes. 6" dia. Mkd. W60 MJCC brs. S.23 50'E.10.8 vrs. arge stone mound brs. S.56 30'E. 372 varas, Said monument is 22feet square at base and 32 feet high a 4"x4" pine post at the N.E. of Sur. No. 66 Blk No. 20 Lavace Navigation Co. is East 152 varas and North 73 varas from corner. Said post is mak. 66 on S. W. face 65 on the S. E. face 72 in N. E. face and 71 one the N. W. Face. Survey finished Apr. 11. 1908 Corner established on Apr. 13, 1908.

> J.A. Orr Z. Robertson Jim Sears D. B. Tucker

Chain Gariers.

Rodmen

S. E. Wright) Marker

We, W. S. McClung Special Surveyor for County boundary Borden Co. Texas. T. H. Seay Special Surveyor County Boundary Howard County Texas. do hereby certify that the foregoing survey was made by us in the field on the ground according to law with the chain carriers rodmen and markers duly qualified and that the limits boundaries and corners with the marks Natural and artificial are truly and correctly described as set forth in the foregoing field notes in Plat No. 1 accompanying same.

Given under our hands this 25th day of April, A. D. 1908.

D. H. Search (Special Surveyor for County Boundary Howard

<u>MCClassicounty boundary Borden</u>

(County Texas.

I, T. H. Seay, County Sarveyor of Howard County Texas, and Surveyor for Howard Land Disctrict do hereby certify that I have examined the foregoing field notes and find them correct and that they are on record in my office in record of field notes No.1 pages 180-189 Howard County Texas.

Given under my hand this 25th day of Apr. A. D.1908.

counter 50622

County Surveyor of Howard County, Texas.

April 11th, 1908.

(Continuing line on secant S.89 59'30"W. through large farm 1901 varas 53rd((set a stake on parallel on intersection with secant.

(Continuing line on secant S.89 59'50"W. crossing wagon road in lane 54th (passing through farm 1901 varas set a stake on parallel 2.13 feet (North of secant in field sandy soil.

(Turn new secant and continue line N. 89 58'20"W. 1901 varas set stake 55th((on parallel at intersection of secant and parallel in open prairie (Continuing line on secant N.89 58'50"W. passing through farm 1901 56th(a (varas set stake 1.27 feet South of secant on parallel.

(Continuing line on secantN.89 59'30" W. crossing a draw Co South 57th((1901 varas set a stake on parallel 1.27 feet South of secant.

(Continuing line on secant West crossing a draw South of big tank 58th((1901 varas set a stake 1.27 feet South of secant on parallel. o

(Continuing line on secant S.89 59'30"W. 1901 varas set a stake on 59th((parallel at intersection of secant and parallel

Continuing line on secant S.89 58'50"W crossing drain Co. South and crossing Willow Creek seven times 1901 varas set a hub on secant We secured a sand stone 2 feet x 6 inches dress the face of stone and draw two lines across the face of same crossing each other at right angles. Place said stone in pit North of hub. The center of said stone at the intersection of the lines being placed 2.13 feet North of hub on secant. The S. W. corner of stone mkd. Howard Co. The N. W. quarter of said stone is marked Borden Co. W.S.Mc and the date 1908 on West half of same. We placed the said stone for the N. WE. Corner of Howard County and the S. E. corner of Borden County. We set a stone in ground on South side of corner stone and against same 22 feet x 1 foot by 6 inches mkd. L X M W . set another stone 22feet x 1 foot x 5 inches marked E L B C on West face 60 varas North of corner set another stone 2 feet z 1 foot x 5 inches marked E L H C on West face. 60 varas South from corner. From said corner a large atone set in the ground in a large stone mound brs. N.38 56'W. 647 varas a pit filled with broken stone where a large stone is placed in 1907 by H .. W. Stonham for the N. W. Corner of Mitchell County brs. N. 150 45'W. counter 50621

n'I

(Continuing line on secant N.89 59'50" W. crossing drain Co. North (44th(Ascending and descending hill 1901 varas. Set a stake on parallel (1.27 feet South of secant on West slope of hill.

(Continuing line on secant N.98 59'30 W. descending hill and high (bluff crossing deep creek, crossing point of hill and small canyon 45th (and ascending hill 1901 varas set a stake on parallel 1.70 feet

(South of secant on point of divide, sandy soil, Mesquite timber.

(Cold and raining.Camped for night.)

April 10th 1908.

(Continuing line on secant West crossing Colorado River 1901 varas (46th(set a stake on parallel 1.27 feet South of secant on point of divide (South of river.

(continuing line on secant S.89 59'30 W. descinding rocky hill and (crossing Colorado River passing through flat valley at 1380 varas 47th (cross Colorado River and ascend abrupt rocky bluff and sand hill (height of hill abave bank of river 91 feet at 1901 varas set a (stake on parallel at intersection with secant, in firm sandy siol.

(Continuing line on secant S.89 58'50"W. over rolling sandy soil 48th((1901 varas set a stake on parallel 2.13 feet North of secant. (Turn new secant and continue line N.89 58'20"W. passing through a (field and descending rocky hill, covered with growth of scrubby Cedar 49th)

(crossing Colorado River 1901 varas set a stake on parallel at ((intersection of secant and parallel.

(Continuing line N.89 58'50"W. crossing Colorado River, passing (over point of rocky hills and recrossing Colorado River 1901 varas 50th((set a sand stone in sandy land marked 50 MW on parallel 1.27 feet (South of secant.

(Continuing line on Secant N.89 59'30"W. through shinery sandy soil 51st(1901 varas set a stake on parallel 1.70 feet South of secant in (a farm.

(Continuing line on secant West crossing Colorado River and ascending (abrupt rocky hill 1901 varas set a stake on parallel 1.27 feet South (of secant.

Camped for the night, determined true Meridian observing polaris (Magentic declination 10°54'E. cuntursoper (Continuing line on secant N.89 59'30" W. 1901 varas set a stake on 33rd(parallel 1.70 feet South of secant on open prairie, rolling dark soil. (Continuing line on secant West through farm 1901 varas set a stake 34th((on parallel 1.27 feet South of secant in field.

(Continuing line on secant S.89 59'30"W. crossing wagon road in lane (about 200 varas North of C"urch house passing through field and des-35th (cending rocky hill and crossing two drains Co.S.1901 varas set a stake (on parallel at intersection with secant on East slope of hill. (Continuing line on secant S.89 58'50"W. descending hill and crossing 36th (drain Co. South 1901 varas set a stake 2.13 feet North of secant

(on parallel in Valley.

(Turn New secant and continue line N.89 58'20" W. passing over 37th(ridge through a farm crossing a wagon road in a lane 1901 varas (set a stake on parallel at intersection of secant.

(Continuing line on secant N.89 58 50 W. passing through farm and 38th(over hill and at 1901 varas set a stake on parallel 1.27 feet South (of secant in a field.

(Continuing line on secant N.89 59'30" W. crossing wagon road in lane 39th (passing through farm 1901 varas set a stake on parallel 1.70 feet

(South of secant in low firm flat Mesqt. Timber.

(Continuing line on secant West crossing branch, crossing wagon road (40th(in lane, passing three houses and large farm on the left 1901 varas (set a stake on parallel 1.27 feet South of secant.

(Camped for the night. Cloudy could not get observation on Polaris. April 8th, 1908.

(Continued line on secant S.89 59(30 W. crossing creek three times. 41st(1901 varas set a stake on parallel at intersection of secant and (parallel.

(Continuing line on secant S.89 58'50" W. crossing same creek 1901 (42nd (varas set a stake 2.13 feet North of secant on parallel on divide (about 300 varas South of school house.

(Turn new secant and continued line N.89 58'20" W.crossing Snyder (and Colorado wagon road in lane about 350 varas South of bridge 43rd((passing through farm 1901 varas erect a stone mound on parallel

(at intersection with secant on side of rocky hill

705

(April 6th, 1908.

(Turn angle from Meridian to secant checked to precision and continue 23rd line on secant S.89 58'30" W. passing through farm crossing drain (corse North 1901 varas set a stake on secant at intersection with (parallel on West slope of rocky ridge.

(Continuing line on secant S.89 58'50"W. crossing branch Co. North 24th passing over ridge and crossing an other branch 1901 varas set a stake (in field 2.13 feet North of secant on parallel.

(Turn new secant and continue line N.89 58'20" W. crossing creek CQ N.E. 25th((1901 varas set a stake on parallel at intersection with secant

(Continuing line on secant N.89 58'50" W. crossing drain Co. S. E. (26th(a scending rocky slope crossing small canyon 1901 varas set a stake ((on parallel 1.27 feet South of secant.

(Continuing line on secant N.89 59'30 "W. crossing two small canyons (27th(1901 varas set a stake on parallel 1.27 feet South of secant in head (of small canyon.

(Continuing line on secant West crossing wagon road in lane Co. N. & S.

28th (crossing another wagon road in lane Co. E. & W. 1901 varas set a stake (on parallel 1.27 feet South of secant in open prairie.

(Continuing line on secant S.89 59'30"W. over opeb prairie 1901 varas (29th(set a stake on parallel at intersection with secant.

(Continuing line on secant S.89 58'50 W. crossing wagon road in lane (Co. N. &. S.1901 varas set a stake on parallel 2.13 feet North of secant 30th (from which the S. W. Cor.of Fisher County as placed by J.P.Bayler brs. (N.23 42' W. 377 varas.

(April 7th, 1908.

Night before being cloudy could not get observation on polaris. We turn to new secant from former line and continued line N.89 58' 31st 20" W. at 498 varas cross the Roscoe-Snyder and Pacific Rail Road Corse S42 57'E. and N.42 57'W.at 1901 varas set a stake on parallel at its intersection with secant in open prairie, firm dark soil. (Continuing line N.89 58'50"W. 1901 varas set a stake on West slope 32nd 1.27 feet South of secant on parallel open prairie, firm dark soil.

74

(1.27 feet South of secant on East slope in sandy soil Mesquite timber (Continuing line on secant N.89 59 30" W. passing through farm 1901 15th (varas set a stake on parallel 1.70 feet South of secant in valley firm (soil Mesquite timber.

(Continuing line on secant West at 388 varas cross the Kansas City Orient and Mexico Railway Co. N. & S. at 1660 varas cross a wagon 16th road in a lane North of a bridge crossing a branch and crossing a creek twice 1901 varas set a stake on parallel 1.27 feet South of secant.

(continuing line on secant S.89 59'30" W. at 90 varas cross creek, (crossing same creek a agin crossing an other creek twice 1901 varas 17th (set a stake on secant at intersection with parallel in Valley firm (dark soil, heavy Mesquite timber.

(Continuing line on secant S.89 58'50"W. crossing creek three times 18th 1901 varas set a stake on parallel 2.13 feet North of secant in Valley (determine true Meridian by observation on polaris.

April 5th,1908, checked last work from Meridian thus established, turned new secant and continue line N.89 58'20" W. crossing rock point and a 19th fence, crossing rocky ridge descending hill into valley and crossing wagon road in lane 1901 varas set a stake on secant at intersection with parallel in a field.

(Continuing line on secant N.89 58'50"W. at 1901 varas set a stake on 20th(parallel 1.27 feet South of secant in Valley.

(Continuing line on secant N.89 59'30"W. crossing a rocky point and (21stcrossing same branch 1901 varas set a stake on parallel 1.70 feet

(South of secant.

(Continuing line on secant West crossing branch and ascending table (lands 1901 varas set a stake on parallel 1.27 feet South of secant 22nd (in black tight land on divide on East side of a lane, camped for the (night, set hub on secant determine true Meridian by observing polaris. (Continuing line on secant S.89 59'30 W. at 1090 varas cross a creek 5TH.(Co. North 1901 varas set a stake on secant at intersection of secant (and parallel.

(Continuing line on secant S.89 58'50"W. at 1260 varas cross the Texas (and Pacific Eailway Corse N. W. 1901 varas set hub tack in top at end of (secant set mile stake on standard parallel 2.13 feet North of secant (hub camp for the night established true Meridian by observing polaris. (April 1st, 1908, turn angle from the Meridian thus established N.89 58' (20" E. to check former work found same correct.

7th. (Turn New secant from the Meridian N. 89 58'20"W. and continue line through mes. flat passing on the North side of a tapk and passing over a hill 1901 varas set a stake on secant at intersection with parallel.
8th. (Continuing line on secant N.89 58'50"W. passing over hill crossing creek 1901 varas set stake in farm 1.27 feet South of secant an parallel (Continuing line N.89 59'30"W. at 233 varas cross the Texas and Pacific Rail Way passing through heavy Mesquite, Hackberry and China timber at 1290 varas cross a creek corse worth at 1901 varas set a stake 1.70 feet (South of secant on parallel.)

(Continuing line on secant West crossing creek Co. S. E. 1901 varas set a 1Cth(stake on parallel 1.27 feet South of secant on the brow of hill sloping (to the East.

(Continuing line on secant S.89 59'30"W. crossing drain Co. South at 11th 1800 varas cross a branch 1901 varas set a stake on secant at intersection with standard parallel.

(April 2nd and 3rd raining could not work, could not get observation (on polaris.

(April 4th, 1908, continuing line on secant S.89 58'50" W. crossing 12th branch Co. South 1901 varas set a stake 2.13 feet North of secant on parallel.

(Turn new secant N.89 58'20"W. and continue line crossing two drains 13th(Co. South 1901 varas set a stake in a new farm on secant at its inter-(section with standard parallel.

(Continuing line on secant N.89 58'50" W. crossing two drains through 14th(farm and crossing a road in lane 1901 varas set a stake on parallel

counter 50/01/

2 Borden & Howard Borden Co Bary Line 2 See also Map K-7-91 Conn. Line 1110 counter 506 24