

REPORT OF SURVEY OF EAST
LINE OF HANSFORD COUNTY, TEXAS.

STATE OF TEXAS,)
COUNTY OF HANSFORD.)

TO THE HONORABLE COUNTY COURT OF HANSFORD COUNTY:

In compliance with your Order to establish and mark the east boundary of Hansford County; We, the undersigned Licensed Land Surveyors met at the South-east corner of Hansford County at 1:00 o'clock P.M. on the 21st day of February A.D. 1929, that being the place and time designated in your order.

By agreement we adjourned to meet the 21st day of March at the North-east corner of Hansford and North-west corner of Ochiltree Counties, being 30 miles west from the North-west corner of Lipscomb County, a large stone set by W.D. Twichell in the year 1897; from which Clark's Monument No. 10 bears west 363.7 varas. (This monument No. 10 is now marked by concrete monument about 30" high set by U.S. G.L.O. Surveyors) At this time we proceeded to lay out and mark the said boundary line in accordance with our findings.

A full description of said survey is given in the following 3 pages of field notes and plat hereto attached marked EXHIBIT "A" and EXHIBIT "B" respectively.

Respectfully Submitted,

T. D. James

Licensed State Land Surveyor, representing Hansford County, Texas.

Robert C. Allen

Licensed State Land Surveyor, representing Ochiltree County, Texas.

Exhibit "A"

FIELD NOTES OF THE SURVEY OF
West Line of Ochiltree County and
East Line of Hansford County

as SURVEYED by

T. O. JAMES, Licensed Land Surveyor, representing Hansford County and
RUPERT C. ALLEN, Licensed Land Surveyor, representing Ochiltree County.

POLARIS OBSERVATION taken at the Northwest corner of Ochiltree and
Northeast corner of Hansford Counties at large stone set by W. D.
Twichell, marked "30-0" on East side and "H" on West side, from which
Clarke Monument No. 10 bears West 363.6 varas.

COURSE OF COUNTY LINE bears S. $0^{\circ} 04' 18''$ W.

Mile No. 1.

Thence S. $00^{\circ} 04' 18''$ W. along west line of Survey 7, Block Z,
Ochiltree County and East line of Survey 22, Block 1, P.F.S. Hansford
County at 120 varas pass 2" galvanized pipe 36" long with 6" turn at
bottom set on small knoll 1242 varas north line Section 1, Block 45,
H. & T.C.Ry.Co. grant from which N.E. corner Section No. 1 bears N. 89°
 $20'$ E. 963.7 varas, S.W. corner 1 bears S. $89^{\circ} 20'$ W. 952.3 varas, 1900.8
varas to mile post No. 1, a 2" galvanized pipe set & E. Md. 2 feet high.

Mile No. 2.

At 1261.2 varas to N. Line Survey 10, said Block 45 1900.8
varas to mile post No. 2 a 2" galvanized pipe set & E. Md. 2 feet high

Mile No. 3.

At 1247 varas to North line Section 11, Block 45, 1900.8 varas
to mile post No. 3 a 2" galvanized pipe set & E. Md. 2 feet high

Mile No. 4.

At 1281.8 varas to North line Section 20, Block 45, 1900.8 varas
to mile post No. 4 a 2" galvanized pipe set in draw & E. Md. 2 feet high.

Mile No. 5.

At 850 varas on North slope of high hill 1316.9 varas to North line
Section 21, Block 45, from which N.E. corner 21 a stone Md. bears
N. $89^{\circ} 20'$ E. 1030 varas, the N.W. corner 21 bears S. $89^{\circ} 20'$ W. 875
varas, 1900.8 varas to mile post No. 5 a 2" galvanized pipe & stone
Md. & E. Md. 2 feet high

Mile No. 6.

At 1341.1 varas to North line Section 30, Block 45, 1900.8 varas
to mile post No. 6 a 2" galvanized pipe & stone Md. 2 feet high

Mile No. 7.

At 1365.8 varas to North line Survey 31, Block 45, 1900.8 varas
to mile post No. 7 a 2" galvanized pipe set & rock Md. 2 feet high

Mile No. 8.

At 1378.8 varas to North line Survey 1, Block 2, Washington
County R.R.Co. Grant from which the N.E. corner 1 a stone set bears
N. $89^{\circ} 20'$ E. 1100 varas, N.W. corner 1 a stone set bears S. $89^{\circ} 20'$
W. 805 varas, 1900.8 varas to mile post No. 8 a pipe set & E. Md. 2
feet high

Mile No. 9.

At 1390.8 varas to North line Survey 4, Block 2, 1900.8 varas
to mile post No. 9 a 2" pipe set & E. Md. 2 feet high

Mile No. 10.

At 1392.6 varas to North line Section 5, Block 2, from which N.E. corner Section 5 bears North $89^{\circ}20'$ E. 1151 varas, N.W. corner Section 5 bears S. $89^{\circ}20'$ W. 761 varas, 1900.8 varas to mile post No. 10 a 2" pipe set & E. Md. 2 feet high

Mile No. 11.

At 1391.8 varas to North line Section 8, Block 2, 1900.8 varas to mile post No. 11 a 2" pipe set & E. Md. 2 feet high

Mile No. 12.

At 1376.8 varas to North line of Survey 9, Block 2, 1900.8 varas to mile post No. 12 a 2" pipe set & E. Md 2 feet high

Mile No. 13.

At 1376.8 varas to North line Section 11, Block 2, 1900.8 varas to mile post No. 13 a 2" pipe set & E. Md. 2 feet high

Mile No. 14.

At 1380 varas to North line of Section 22, Block 2, 1900.8 varas to mile post No. 14 a 2" pipe set & E. Md. 2 feet high

Mile No. 15.

At 1379.5 varas to North line of Section 23, Block 2, 1900.8 varas to mile post No. 15 a 2" pipe set & E. Md. 2 feet high

Mile No. 16.

At 1379.1 varas to South line Section 23, Block 2, W. C. R.R. Co. Grant & North line Survey 10, Block 4T, T. & N.O.R.R.Co. Grant from which the S.E. corner 23 bears N. $89^{\circ}10'$ E. 1306 varas, the S.W. corner 23 a $\frac{3}{4}$ " pipe bears S. $89^{\circ}10'$ W. 594 varas, the N.E. corner Survey 10, Block 4T, ~~XXXX~~ a 2" pipe at fence corner bears N. $89^{\circ}10'$ E. 1032.5 varas, the N.W. corner of Survey 10, Block 4T, bears S. $89^{\circ}10'$ W. 870.5 varas, 1900.8 varas a 2" pipe & E.Md. 2 feet high

Mile No. 17.

At 501 varas cross center line of N.T. & S.Fe R.R. track, from which Railroad mile post No. 76 bears N. $58^{\circ}59'$ E. 535.7 varas 1385.2 varas to North line of Section 27, Block 4T, 1900.8 varas to mile post No. 17 a 2" pipe & E. Md. 2 feet high

Mile No. 18.

At 1394.9 varas to N. Line Section 43, Block 4T, 1900.8 varas to mile post No. 18 a 2" pipe set & E. Md. 2 feet high.

Mile No. 19.

At 1404.8 varas to North line of Section 52, Block 4T, 1900.8 varas to mile post No. 19 a 2" pipe set & E. Md 2 feet high

Mile No. 20.

At 1407 varas to South line Section 23, Block 4T, 1900.8 varas to mile post No. 20 a 2" pipe set & E. Md. 2 feet high

Mile No. 21.

At 1406.8 varas to North line Section 82, Block 4T, 1900.8 varas to mile post No. 21 a 2" pipe & E. Md. 2 feet high

Mile No. 22.

At 1900.8 varas to mile post No. 22 a 2" pipe and E. Md. 2 ft. high

Mile No. 23.

At 1900.8 varas to mile post No. 23 a 2" pipe set & E. Md. 2

feet high

Mile No. 24.

At 1900.8 varas to mile post No. 24 a 2" pipe set & E. Md. 2 feet high

Mile No. 25.

At 1900.8 varas to mile post 25 a 2" pipe set & E. Md. 2 feet high

Mile No. 26.

At 1408.3 varas to South line Section 142, Blk. 4T & North line Survey 1, Block 2, J.F. Torrey Grant from which S.W. corner 142 bears S. 89° 25' W. 611.5 varas same being the N.W. corner Survey 1, Block 2, J.F. Torrey grant At 1900.8 varas to mile post No. 26 a 2" pipe & E. Md. 2 feet high

Mile No. 27.

At 1900.8 varas to mile post No. 27 a 2" pipe & E. Md 2 ft. high

Mile No. 28.

At 1421.8 varas to North line Survey No. 25, Block R, 1900.8 varas to mile post No. 28 a 2" pipe & E. Md 2 feet ~~long~~ high

Mile No. 29.

At 1422.8 varas to North line of Survey 46, Block R at 1900.8 varas to mile post No. 29 a 2" pipe & E. Md. 2 feet high

Mile No. 30.

At 1423.8 varas to mile post No. 30 a 2" pipe & E. Md. 2 feet high

30 miles plus 1273.1 varas to Concrete monument set 30" high marked "O.H.H. & R." the S.W. corner Ochiltree, S.E. corner Hansford, N.E. corner Hutchinson and N.W. corner of Roberts Counties, from which a concrete monument by Twichell bears South 40.3 varas.

All of the above mentioned pipe set for mile post are from 30" to 36" in length, and marked "O" on the E. side and "H" on the W. side.

The acreage in Ochiltree and Hansford Counties in Surveys traversed by the line is shown on the attached plat marked "Exhibit B"

Dated January 7th, A.D. 1930.

T. D. James
 Licensed Land Surveyor, representing
 Hansford County, Texas.

Rupert C. Allen
 Licensed Land Surveyor, representing
 Ochiltree County, Texas.

Осцилляторная станция, Техаса.

Лицензия на использование, Техаса.

Handwritten signature

Ханфорд Коунти, Техаса.

Лицензия на использование, Техаса.

Handwritten signature

Dated January 27th, A.D. 1930.

Witnessed by the line is shown on the attached plat marked "Exhibit B" the section in Oscillator and Hanford Counties in the State of Texas to 30" in length and marked "O" on the E. side and "H" on the W. side. All of the above mentioned pipe set for mile boat are from 30" concrete monument by Mitchell bears south 40° 2' west.

Corner intersection and W.M. corner of Roberts County, Texas which a corner marked "O.H.H. & B." the S.W. corner Oscillator, S.E. corner Hanford, Tex. 30 miles plus 1323.1 acres to concrete monument set 30" high

Counter 54274

high

At 1432.8 acres to mile boat No. 30 & S. pipe & E. Mg. 3 feet
Mile No. 30.

acres to mile boat No. 30 & S. pipe & E. Mg. 3 feet high

At 1433.8 acres to North line of Shaley & Block B at 1300.8
Mile No. 30.

acres to mile boat No. 30 & S. pipe & E. Mg 3 feet high

At 1431.8 acres to North line Shaley No. 30, Block B, 1300.8
Mile No. 30.

At 1300.8 acres to mile boat No. 30 & S. pipe & E. Mg 3 feet high
Mile No. 30.

S. pipe & E. Mg. 3 feet high.

Block S, T.E. Lolley Grant At 1300.8 acres to mile boat No. 30 & Roberts S. 80. S2. W. 11. 2 acres same being the N.W. corner Shaley 1, line Shaley 1, Block S, T.E. Lolley Grant from which S.W. corner 143
Mile No. 30.
At 1408.2 acres to South line Section 14S, B1K. 4L & North

feet high

At 1300.8 acres to mile boat 30 & S. pipe set & E. Mg. 3
Mile No. 30.

3 feet high

At 1300.8 acres to mile boat No. 30 & S. pipe set & E. Mg.
Mile No. 30.

feet high

Handwritten: Hanford Co. Plat Line 3

Handwritten: 30

Handwritten: 100

30

100