

Howard Co. (2) Bdry. line
County Line
Between
Howard and Mitchell
Counties -

Filed Mch 20th 1922

J. R. Robison Comm
Clerk

Filed for the purpose only
of showing the marking of
the line by the two Counties -
See carbon copy of letter attached
Clerk

Cop. F/MS	\$2.50
" Plat.	1.50
	<hr/> 4.00

4

HOWARD & MITCHELL
COUNTIES TEXAS.

By Resolution passed at a meeting of the Commissioner's Court in the above named counties, December 6th, 1921, a Survey was ordered to be made between said Counties, the survey to conform with the notes and data furnished by the LAND DEPARTMENT at Austin, the survey to conform with the N.E. Cor. of Howard County and the N.W. Cor. of Mitchell County, and with the S.E. Cor. of Howard County and the S.W. Cor. of Mitchell County.

The Field Notes and Plat with Description of the Survey made from the data, was carefully made in accordance and is herewith submitted beginning Dec. 20th, 1921-

R. S. Fuller
R. S. Fuller, C. E.
Special Surveyor
For Howard & Mitchell
Counties, Texas. Jany 21" 1922.

FIELD NOTES

A Survey to Establish the East boundary line of Howard County which shall be the West boundary line of Mitchell County, Beginning at the S.E. Cor of Howard County which shall be the S.W. Cor. of Mitchell County. The established Boundry to connect with the N.E. Cor. of Howard County, which shall be the N.W. Cor. of Mitchell County.

Dec. 20th, 1921.

Beginning at the S.E. Corner of Howard County, which is the S.W. Corner of Mitchell County, A large Sand Stone firmly set in the ground showing 7"x 14" above the surface 14" high marked on its N.W. corner S.E. Cor H.Co. on its N.E. Cor, S.W. Cor. M.Co, on its South Face, S.C.L. a cedar post 8" in dia. 4 ft high is set along side the Rock corner. This corner is fully identified by the data at hand and is further checked by measurements along the line East for three miles on the N. line of Sterling Co and S. line of Mitchell Co. For the purpose of this Survey a Mag. Va, at $10^{\circ} 15'$ E. is used to establish a Tangent to be produced to the North line of the County, this line is carefully measured and Temporary corners marking each mile for a full distance of 30 miles (2880 ft.)^{1036 yrs} The Stone marking the N.E. Cor of Howard County and the S.E. Corner of Borden County, this corner is West of this line 677.8 vrs.

This closing will be used to establish a true line between corners and a true boundary line between Mitchell and Howard Counties, making the corner at the North end of the survey the N.E. Cor. of Howard Co, the N.W. Cor. of Mitchell Co, the S.E. Cor. of Borden Co, and the S.W. Cor of Scurry Co, identified by a large Sand Stone 2 ft.x 2 ft. laying flat surrounded by small stone even with the surface, at the South side of the stone, a large sand stone firmly set, showing 7"x 14" 16" above ground, marked on S. face L.x M.W. the N.E. Cor. of Sec. 66, Lavaca Nav. Co, Blk. 20 is East 151 vrs, and North 73 vrs, a sawed post 4"x 4" 16" above ground firmly set on the S. bank of Willow Cr. marking the N.E. Cor, Sec. 66, the N.W. Cor Sec. 65, the S.E. Cor Sec. 71 and the S.W. Cor. of 72.

The initial and objective corners having been fully identified, the true boundary line between Howard & Mitchell Counties is run by Beginning at the S.E. Cor. of Howard Co, which is the S.W. corner of Mitchell Co, on the N. line of Sterling Co.

The Magnetic Va. of $9^{\circ} 35'$ E. the Boundary line would show True North Line

Howard Co. Bdry Line 2

T³

counter 55113

From Corner North	1664 vrs.	Cross N. line Sec. 146, 953 vrs west of the N.E. Cor of 146 W. & N.W. R.R. Co Block 29.
	1900 "	a 1½" galvanized iron pipe 36" long is driven 2 ft in ground for Cor. on Co. line 1 Mile North.
North	1204 vrs	Cross fence line E. & W.
	1664 "	Cross N. line Sec. 119 W & N.W. R.R. Block 29 960 vrs W. of N.E. Cor.
	1900 "	a 1½" Galv. iron pipe 36" long driven 2 ft in ground for cor. on Co. line 2 Mi. N.
North	1664 vrs	Cross N. line of Sec. 118 W. & N.W. R.R. Blk. 29, 965 vrs, W. of N.E. Cor.
	1900 "	a 1½" Gal. I. Pipe 36" long driven 2 ft. in ground for Cor on Co. line 3 Mi. N.
North	1664 vrs	Cross N. line Sec. 91, W & N.W. R.R. Co, Blk 29, 970 vrs. W of N.E. Cor.
	1900 "	a 1½" Galv. Iron pipe 36" long driven 2 ft in ground for Cor. on Co. line 4 Mi. N.
North	120 vrs	Cross fence line E. & W.
	320 "	" Drain S.W. to N.E.
	1664 "	" N. line of Sec. 90 W. & N.W. R.R. Blk. 29.
	1900 "	a 1½" Galv. I. pipe 36" long driven 2 ft in ground for Cor. on Co. line 5 Mi. N.
North	63 vrs	The S.W. Cor. of Smiths cultivated field is E. 115 vrs.
	1649 "	Cross N. line of Sec. 63 W & N.W. R.R. Blk. 29, 965 vrs W. of the N.E. Cor.
	1900 "	a 1½" Galvanized Iron pipe 36" long driven 2 ft. in ground for Cor. on Co. line 6 Mi. N.
North	132 vrs	Cross fence course E & W.
	1800 "	" Evidence of the S. line of survey of Block 30 T & P. R.R. T.I.S. 820 vrs N 75°E from a cor. of rocks piled for Cor. for S.W. Cor. 47 T & P R.R. Blk. 30 T.I.S.

	1900 vrs.	a 1½" Galv Iron pipe 36" long driven 2 ft. in ground for Cor. on Co. line 7 Mi. N.
North	1880 vrs	Cross N. line Sec. 47 T & P. R.R. Blk. 30 T.I.S. 482 vrs.S. 75° W. from the N.E. Cor.
	1900 "	a 1½" G.I.P. 36" long driven 2 ft. in ground for cor. on Co. line 8 Mi. N.
North	756 vrs	Cross dividing fence between Wilson & H.S. pastures.
	1016 "	Cross Drain.
	1885 "	Cross N. line Near the Cor. of Secs. 35, 36, 37, 38. Veal Crk East course E.
	1885 "	
	1900 "	The S.E. Cor of Sec. 35 is S. 8 vrs. the evidence of the corners are obliterated by flood
		A 1½" G.I.P. 36" long is driven 2 ft in ground for Cor on Co. line, 9 Mi. N.
North	1891 vrs	Cross N. line Sec. 36 T & P. R.R. Blk. 30, T.I.S. 482 v. N. 74° E of the N.W. Cor.
	1900 "	A 1½" G.I.P. 36" long is driven 2 ft. in ground for Cor. on Co. line 10 Mi. N.
North	518 vrs	Cross Fence N.E. & S.W.
	536 "	" Dugout Creek.
	1900 "	A 1½" G.I.P. 36" long is driven 2 ft. in ground for Cor. on Co. line, 11 Mi. N.
North	1900 vrs	A 1½" G.I.P. 36" long is driven 2 ft. in ground for line Co. corner 12 Mi. N.
North	1900 vrs	Cross E. line of Blk 30 T & P. R.R. Survey, S. 16° E 150 vrs from N.E. Cor. Sec. 13, A 1½" G.I.P. 36" long is driven in ground for Cor, on Co. line 13 Mi. N.
North	1900 vrs.	A 1½" G.I.P. 36" long is driven 2 ft. in ground for Cor, on Co. line 14 Mi. N.
North	1900 vrs	A big rock in the fence line running N. 15 W. is west of this Cor. 216 vrs.
North	1900 vrs	A ½" G.I. pipe 36" is driven 2 ft in ground for Cor on Co. line 15 Mi. N.

North	600 vrs.	Cross Fence running N 74°E. & S. 74° W. on the North line of Block 29 T.P.R.R. Survey 1.S. 816 vrs. S.74 W. from N.E. Cor, Sec. 6.
	1900 "	A marked stone ("16 M") in a mound of stone for cor, on Co. line, A large monument 5' sq. 5' high is built 25 vs, N. on line at the edge of mountain.
North	369 vrs	Cross N. line of Sec. 43 T & P.RR Blk 29, T.I.N. 527 vrs S. 74 W. from the N.E. Cor
	534.6 "	Cross main line of Texas & Pacific Rail Road, N. 72° 20 E.
	569 "	Bankhead Highway -To El Paso.
	1900 "	A 1½" Galv.Iron pipe 36" long driven 2 ft. in ground for Cor on Co. line 17 Mi. N.
North	200 vrs	Top of Iatan Mountain.
	1900 "	On top of Mt. a mkd stone for cor, on line 18 M. N. a large pile of stones on N & S. edges of the Mountain.
North	1900 vrs	A 1½" G.I.P. is set on the line of the County Road between Big Springs & Colorado, at a point 280 vrs. N. of the 19 Mi. Cor.
North	280 vrs	Cross the Big Springs & Colorado Co.Road, a 1½" G.I.P. 36" long is driven 2 ft. in ground for a point on the Co. line.
North	1900 vrs	A 1½" G.I.P. 36" long driven 2 ft. in ground for Cor. on Co. line, 20 Mi. N.
North	452 vrs	Cross Fence line bears S. 68°30 W. & N. 68°30' E. no evidence of corners can be found on this or the fence running S.22°E.
	1900 "	A 1½" Galv Iron pipe 36" long is driven 2 ft. in ground for Cor on Co. line for 21. Mi. N.
North	650 vrs	Cross N. line of Sec. 16, T & P. R.R. Blk 29 T.I.N., 110 vrs N. 74° E from the N.W. Cor.
	1900 "	A 1½" G.I.P. 36" long driven 2 ft. in ground for Cor on Co. line 22 Mi. N.
North	1900 vrs	A G.I.P. 36" long driven 2 ft. in ground for Cor. on Co. line 23 Mi. N.

North	1180 vrs.	Cross the North line of the T & P. R.R. Survey of Block 29, T.I.N. 800 vs. S. 74°W. from the N.E.Cor.Sec. 4.
	1900 "	A 1½" Galv.iron pipe 36" long driven 2 ft. in the ground for Cor. on Co. line 24 Mi. N.
North	950 vrs	Cross the N. line of Sec. 40 H & T.C. R.R. Block 26, 1820 vs, West of the S.E. Cor Sec. 33, H & T.C. R.R.Blk 26.
	1900 "	A 1½" G.I.P. 36" long driven in ground for cor. on Co, line 25 Mi. N.
North	990 vrs	Cross the N. line Sec. 33, H & T.C. R.R. Blk 26, 1800 vrs W. of the N.E. Cor of Sec. 33.
	1900 "	A 1½" G.I.P. 36" long driven in ground 2 ft. for Cor on Co. line 26 Mi. N.
North	1010 vrs	Cross N. line of Sec. 16 H & T.C.R.R. Blk 26, 1800 vrs W. of the N.E.Cor of Sec.
	1900 "	A 1½" G.I.P. 36" long driven in ground 2 ft. for Cor on Co line 27 Mi. N.
North	1035 vrs	Cross N. line of Sec. 9 H & T.C.R.R. Blk 26, 1830 vrs, W. of the N.E. Sec. 9, a 1½" Galv I.pipe 36" long is driven on each side of the County road on line.
	1900 "	A 1½" Galv. I. pipe 36" long driven 2 ft. in ground for Cor, on Co. line 28 Mi. N.
North	1058 vrs	Cross N. line of Sec. 4, H & T.C.R.R. Blk 25, 10 vrs, W. of the N.E. Cor of Sec. 4.
	1900 "	A 1½" G.I.P. 36" long driven 2 ft. in ground for Cor on Co, line N. 29 Mi.
North	1060 vrs	Cross N. line of Sec. 59, and S. line of Sec. 66, L.N. Co, Blk 20, 160 vs, W. of the N.E.Cor. Sec. 59.
	1900 "	A 1½" G.I.P. 36" long driven in the ground 2 ft. for Cor. on Co. line 30 Mi. north from place of beginning.
North	(2880) vrs 1036 Yrs.	The Corner of Howard, Borden, Mitchell and Scurry Counties.

W.G. Harper :
 H.H. McCright :
 W. Goldson : Chainmen
 W.L. Carver :
 W.G. Bond, Flagman

R.S. Fuller
 Special Surveyor
 Howard & Mitchell Cos.
 Texas.

Jany. 20th, 1922.

I, *R.S. Fuller* *Special* County Surveyor, ~~Taylor County~~ *for Howard & Mitchell Counties*, Texas, do hereby certify that the foregoing described Survey was actually made by me on the ground, according to law, on the date and with the Chain Carriers aforesaid, duly qualified, and that all the Corners, Lines, Boundaries and Marks of the same, whether natural or artificial, are truly and correctly described and set forth in the foregoing Plat and Field Notes.

By *R.S. Fuller* Deputy.

R.S. Fuller
 Special County Surveyor, Taylor County, Texas.
 Howard & Mitchell Cos.

F7
 Com. 55117