Field notes South Line Howard Co and North Lines (Parts) Calasscock 3 Sterting Cos-Filed July 20th 1928 J.T. Robison Cour. Clark Photo Capy 7/2 8 00 " " Count order 100 " Plat (3 shots 16" Cantle SS130

R. T. BUCY LICENSED LAND SURVEYOR OF TEXAS

MIDLAND, TEXAS

....

July 18, 1928.

2929

JUL 2 0 1928

Hon. J. T. Robison, Commissioner, General Land Office. Austin, Texas.

Dear Sir:

There will be mailed to you from the County Clerk of Howard County, Texas, a certified copy of Field Notes and a plat showing South line of Howard County and parts of the North line of Sterling and Glasscock Counties, which work was done by W. F. Kellis of Sterling City, Texas, who represented Sterling and Glasscock Counties and me who represented Howard County. We were appointed by the County Courts of said counties and ordered to locate and mark according to law the South boundary line of Howard County. The plat and Field Notes referred to herein are in accordance with Article 1587 R. C. S. of Texas.

Yesterday in company with Mr. Kellis we placed notes and plat for record with County Clerk of said counties, and he is going to write you a letter concerning the field work along this line at a near future date.

By way of explanation to your examining draftsman, I beg to state the following: At the time we were ordered to proceed and work this line there were already in existence, and had been for several years, three county corner monuments: one at Southwest corner of Mitchell, as placed by Kellis & Stoneham in 1906; the second at the Northeast corner of Glasscock County, as placed by T. H. Seay et al; and the third, a red sandstone pier, was set by R. E. Estes and C. B. Collard for the Northeast corner of Midland County in about 1900. These three monuments were supposed to have been placed on a parallel of latitude; however, upon investigation in the field, we found that the monument at the Southwest corner of Mitchell County is actually 33.6 varas South of a six-mile chord of latitude, passing through the two other monuments referred to above; since Mitchell and Howard Counties had agreed prior to our order and appointment that this monument would be their common corner and boundary, you will note that from this point we ran a tangent to the Northeast corner of Glasscock, as referred to, which shows a course of North 89° 47' West. Then from the Northeast corner of Glasscock County West on six-mile chord of latitude, using the sixth mile on South line of Howard County and multiples thereof as angle points, we placed the boundary and mileposts on six-mile chords and projecting a line in the same manner from Southwest corner of Howard County, as located in these notes and shown on the plat, West passing through said Northeast corner of Midland County as located by Estes and



MIDLAND, TEXAS

Page #2 Hon. J. T. Robison

7-18-28

Collard, as shown on the plat.

After examination of these notes and plat, if there need to be any correction, please return same to W. F. Kellis at Sterling City, Texas, stating correction or objection, and he will notify me.

The concrete piers as described in these notes are eight-inch square and thirty inches long and are set in the ground about eighteen inches, and make a very unique boundary monument.

Hoping to be in Austin and to pay your office a visit in the near future, I beg to remain

Yours truly, P.I. Bucy

RTB/S

P. S. It seems from the way most voters in this part of the State talk, there is no doubt but that you will carry this section of the State rather solidly in the coming Primaries. "Uncle Bill" Kellis has spoken of you during our work recently quite a number of times, and he says you will also carry his locality. He regards you as one of his closest friends. R.T.B. MIDLAND, TEXAS

7-18-28

Countures 133

Spage 42 Hon. J. T. Hobison

Collard, as shown on the plat.

After examination of these notes and plat, if there need to be any correction, please return same to W. F. Kells and the statistic for the statistic of the statistic for the statistic of the statistic for the statistic of the statistic for the statistic for the statistic form of the st

The concrete piers as described in these notes are eight-inch square and thirty inches long and are set in the ground shout eighteen inches, and make a very unique boundary monument.

ait in Hoping to be in Austin and to pay your the near future, I beg to remain

Yours truly,

BTB/S

7. 3. It seems from the way most voters in this part of the State talk, there is no doubt but that you will carry this section of the State rather solidly in the coming Primaries. "Uncle Bill" Kellis has spoken of you during our work recently quite a number of times, and he says you will also carry his locality. He regards you as one of his closest friends.

B.T.B

54

line

Bdry

8

Howard

STATE OF TEXAS SCOUNTY OF HOWARD

2. 11 1

Howard La Boy wine 3. . . .

Counter 55134

IN THE COUNTY COURT OF HOWARD COUNTY, TEXAS.

Whereas, heretofore, R.T. Bucy was appointed by this Court to meet the appointed surveyor of Glassock and Sterling Counties, and survey out the South boundary line of Howard County, Texas, which is also a part of the North boundary line of Sterling and Glassock Counties; and,

Whereas, W.F. Kellis, the duly appointed surveyor of Glassock and Sterling Countries, did meet with the R.T. Bucy and they, in accordance with the orders of this Court, survey out the said boundary line lying between said Counties as appears from their report duly filed and recorded in the Minutes of this Court at Page 549 et. seq. in Volume, 2, and,

Whereas, from said report said line so surveyed appears to be the true and correct boundary line of Howard County, Texas, lying between said Counties, and the Field Notes and plat of said boundary line are hereby in all things approved and said boundary line is declared to be the South boundary line of Howard County, Texas.

Witness my hand, officially, this the 14th. day of August, A.D. 1928.

County Judge, Howard County, Tex Texas.

The State of Texas, County of Howard. I,J.I.Prichard,Clerk of the County Courtain and for said County and State,hereby certify that the within page contains a true and correct copy of the approvalfofththe Count of the/boundary line of Howard County, Texas, as same appears of record in Vol.2 pages 549 et seq. Minutes of the County Court,Howard County,Texas.

Given under my hand and seal of office, this 14th.day of Aug.A.D.1928 .

J. Crichard ity Clerk, Howard County, Texas. 2 County

50.07

7 4t. E

line \$ 3 Copy Order County Court Howard County approving Survey of County Line -Files Quegust 17th 1928 J.T. Robison, Cour-Cloth or . 100 Counter 55 136

STATE OF TEXAS.

C.

00

COUNTIES OF HOWARD, STERLING AND GLASSCOCK.

FIELD NOTES OF A SURVEY OF THE SOUTH LINE OF HOWARD COUNTY AND PORTIONS OF THE NORTH LINE OF STERLING AND GLASSCOCK COUNTIES, STATE OF TEXAS.

-0-

STATE OF TEXAS.

0

10

0

COUNTIES OF HOWARD, STERLING and GLASSCOCK.

FIELD NOTES OF A SURVEY OF THE SOUTH LINE OF HOWARD COUNTY AND PORTIONS OF THE NORTH LINE OF STERLING AND GLASSCOCK COUNTIES, STATE OF TEXAS.

Pursuant to an order of the Honorable County Court of Howard County, appointing R. T. Bucy, a Licensed Land Surveyor, of Midland County, Texas, as a Special Surveyor, ordering him to represent Howard County on a survey of the South boundary line of Howard County, and W. F. Kellis, a Licensed Land Surveyor of Texas, Sterling City, Texas, is ordered by the Honorable County Courts of Sterling and Glasscock Counties to represent each of them on that portion of their North lines as adjacent to the South line of Howard County, and the following pages are Field Notes showing work done in obedience to said order.

- - - - - - - -

BEGINNING at a concrete pier marked on the North side Howard and on the South side Sterling, and a pile of large stones: one marked S. W. M. Co. - S. E. H. Co, 1906; one marked N. line S. Co., and from which the East edge of Signal Peak bears North 43° 40' 30" West, and the lowest point in saddle between two low mountain ridges bears North 46° 39' 30" West this point, and land-mark had been set previous to this date as the S. W. corner of Mitchell and S. E. corner of Howard County, and is agreed upon by all counties concerned as being the boundary marker, as hereinabove stated, and is the beginning point of this survey by virtue of said Court order. The above described monument

-1-

is in Survey 146, Block 29, Waco & Northwestern Railway Company, and is 941 varas East of the West line of this survey and is 986.6 varas West of the East line of this survey and where the South line of Howard County crosses the West line of this survey is a point 195 varas North 2° 32' East from a set stone, the S. W. corner of said Survey 146; and of Survey 146, 265.4 acres are in Howard County and 91 acres are in Sterling County.

0

22

0

Mile 1. THENCE North 89° 47' West at 941 varas cross the West line of Survey 146 and at 1360 varas pass a large set stone marked S. Co. L. 4 M. and at 1900.8 varas set a concrete pier 8 x 8 x 30" marked on the North side Howard and on the South side Sterling and on top I, which is on the East bank of Spring Creek and from which a B on a stone bears South 45° 12' West 4 varas, and a K on flat stone bears North 56° 9' West 6.6 varas, and the East point of mountain bears North 47° 38' West.

Mile 2. THENCE North 89° 47' West crossing the West line of Survey 145 123.2 varas North 2° 30' East of its S. W. corner which shows 577.8 acres in Howard County and 62.2 acres in Sterling County; and at 1900.8 varas to a concrete pier, marked as above described, from which a K on an 8" mesquite South 45° 12' East 9 varas and a K on a 12 inch mesquite in a clump of mesquite North 43° 16' West and the East bank of a creek bears West 86 varas, and a set stone bears East 536.5 varas. (This stone is an old land-mark placed on a prior survey of county line connections.)

Mile 3. THENCE North 89° 47' West at 86 varas cross creek and crossing West line of Survey 144 50.2 varas North 2° 28' East of its S. W. corner, which shows 604.8 acres are in Howard County and 35.2 acres are in Sterling County; and West at 1900.8 varas a concrete pier, marked as above described, from which an 8 inch mesquite tree bears South 68° 24' East 24.8 varas and a 7 inch mesquite tree bears

- 2 -

North 47° 26' East 23 varas, and the East end of Hayrick Mountain bears North 4° 51' West, and an East and West fence bears South 21 varas, and an old set stone bears East 525.3 varas.

0

-

0

<u>Mile 4.</u> THENCE North 89° 47' West crossing the South line of Survey 143 at a point 366 varas E_ast of its S. W. corner, and on West crossing the W_est line of Survey 150 at a point 22.7 varas South 2° 27' West of its Northwest corner, which shows 4/10 of one acre of land of Survey 150 in Howard County and 8.8 acres of Survey 143 are in Sterling County; and at 1900.8 varas set a concrete pier, marked as above described, in the North slope of mountain point, from which a B on a flat rock bears South 67° 19' East 4.4 varas, and a K marked on a flat rock bears North 41° 15' West 11.9 varas, and a windmill bears North 80° 21' East, and the East face of Perpendicular Bluff bears North 15° 46' East.

Mile 5. THENCE North 89° 47' West crossing the West line of Survey 151, 96.9 varas South 2° 24' West of its N. W. corner, which shows 18.6 acres of Survey 151 are in Howard County and 621.4 acres are in Sterling County; then on west at 1401.2 varas pass a large stone mound and pile of stone, one large red sandstone marked, N. W. Sterling Co., and other marked, N. E. Glasscock Co. (This monument is in the head of a small canyon and was placed quite a good many years ago by surveyors running the boundary line of the counties adjacent to this parallel of latitude and their survey was begun at the N. E. corner of Coke County and ran West to the border of Texas.) And West at 1694.2 varas cross Roxana's Dutch Shell pipe line 183 varas North 41° 59' East of an angle point where its line from there turns to South 56° 49' West; and in all 1900.8 varas to a concrete pier for the fifth milestone, from which a B on a flat rock bears South 85° 58' East 29.7 varas, and a K on a flat rock bears North 79° 08'

- 3 -

East 86.5 varas, and the West end of Signal Peak bears North 18⁰ 13' West.

0

-

C

Mile 6. THENCE West crossing the West line of Survey 152 which is a point in the center of graded road South 2° 28 West 175.5 varas from its N. W. corner, which shows of Survey 152, 45.5 acres are in Howard County and acres are in Glasscock County and acres are in Sterling County; and West passing a set stone marked, S. Co., at 1900.8 varas a concrete pier marked on the South side, Glasscock, and on the North side, Howard, and on top face, 6, in a brushy flat.

<u>Mile 7.</u> THENCE West at 987 varas cross the West line of Survey 153 at a point 260.4 varas South 2^o 36' West from its N. W. corner, which shows of Survey 153, 73.3 acres are in Howard County and 566.7 acres are in Glasscock County; thence West at 1350 varas the East bank of a draw, and at 1400 varas the West bank of draw, and at 1408.5 varas a large stone marked, C. L. 2; and in all 1900.8 varas to a concrete pier marked on the South side, Glasscock, and on the North side, Howard, and on top, No. 7, from which a windmill at Clay Ranch headquarters bears North 62^o 34' East, and a DO at Durham place bears South 45^o 18' East.

Mile 8. THENCE West at 992.7 varas cross the West line of Survey 154 South 2° 29' West 340.3 varas from a two-inch iron pipe marked, 138-139-154-155, which shows of Survey 154, 101.1 acres are in Howard County and 538.9 acres are in Glasscock County; thence West in all at 1403.5 varas pass a stone marked, S. Co. 8 K; and in all 1900.8 varas to a concrete pier marked, as above described, and with an 8 on top face.

Mile 9. THENCE West at 454.9 varas pass a set stone, and at 996.5 cross the West line of Survey 155 at a point South 2[°] 21[•] West 422.7 varas from its N. W. Corner, which shows of Survey 155, 128.4 acres are in Howard County and 511.6 acres are in Glasscock County; thence on West at 1234 varas pass 13 varas

- 4 -

South of F. H. E. Oil Company No. 2 oil well; at 1408.5 varas pass a set stone marked, C L 4 W; and at 1428.5 pass 22.5 varas South of F. H. E. No. 3 oil well; and at 1621.3 varas pass 30 varas South of F. H. E. No. 4 oil well, and this point is 77 varas North of Coyle & Concord's No. 5 oil well; and in all at 1900.8 varas a concrete pier, marked as above described, with 9 on top face, which is in the back side of Coyle & Concord's field camp, from which Coyle & Concord's water well bears South 65° 43' West 42.1 varas, and a six inch mesquite across the draw bears North 14° 14' West 103.4 varas.

0

-

0

<u>Mile 10.</u> THENCE West at 102 varas cross the draw; at 452.5 varas pass half mile G. Co. stone; and at 946.6 varas cross West line Survey 156, 503 varas South 2^o 27' West of its N. W. corner, which shows of Survey 156, 155.1 acres are in Howard County and 484.9 acres are in Glasscock County; and at 986 varas cross the draw; and at 1020 varas pass a set stone, no marks, in East slope; and at 1405.5 varas pass a set stone marked, C L 5 W K; and at 1900.8 varas mile post No. 10, concrete post with a 10 on top, from which a four inch mesquite **bears** North 73^o 23' East 27 varas, and Magnolia Petroleum Company's No. 3 Dora Roberts bears South 75^o 38' West, and Lockhart et al No. 1 Dora Roberts bears South 52^o 38' East, and a windmill bears South 42^o 04' West.

<u>Mile 11.</u> THENCE West 452.5 varas pass a set stone; and at 993.2 varas cross the West line of Survey 157 at a point 585.8 varas South 2° 31' West of its N. W. corner (which is a set stone by Geo. Williams marked, S W 136, also a twoinch iron pipe); and which shows of Survey 157, 183.3 acres are in Howard County and 456.7 acres are in Glasscock County; and on West at 1405 varas G. Co. milestone; and at 1900.8 varas set concrete pier, marked as above described, No. 11 on top, from which a four inch mesquite bears South 57° 10' West 35.5 varas, and a windmill is North 29° 55' West, an oil der-

rick North 23° 37' West.

0

0

<u>Mile 12.</u> THENCE West at 452 varas pass a set stone half mile G. Co.; and at 1002.5 varas cross the West line of Survey 158 at a point 666.6 varas South 2[°] 26' West from its N. W. corner; also along this line Texas Electric Service Company's high tension line, which shows of Survey 158, 210.8 acres are in Howard County and 429.2 acres are in Glasscock County; then West at 1405 varas pass the seventh milestone Glasscock County survey; and at 1900.8 varas set a concrete pier marked on North side, Howard, on the South side, Glasscock, and on the West side, a triangle, with a 12 on top; from this point a four inch mesquite marked K bears North 85[°] 11' East 45.3 varas, windmill on hill among trees South 27[°] 50' West, and a DO South 5[°] 16' West.

0

<u>Mile 13.</u> THENCE West at 452 varas pass one-half mile G. Co. stone marked C L K; and at 1006 varas cross the West line of Survey 159 at a point 1152 varas North 2° 25' East of its S. W. corner which is a stone marked, N. E. 161, and an iron pipe marked the same, which shows of Survey 159, 238.3 acres are in Howard County and 401.7 acres are in Glasscock County; and on West at 1405.2 varas pass a stone marked, 8 W K; and at 1650 varas cross a creek; and in all 1900.8 varas set a concrete pier marked on top, 13, and otherwise as above described, from which a windmill bears South 7° 41' West, and a DO South 8° 19' East and a four-inch mesquite marked, \overline{XIII} , bears North 66° 49' East 75.2 varas.

Mile 14. THENCE West at 453.4 varas pass a set stone one-half mile G. Co.; and at 1007.8 varas cross the West line of Survey 160 and a point 828 varas South 2[°] 22' West from its N. W. corner, which is a stone marked on the East side, 133, and on the West side, G W, which shows of Survey 160, 265.5 acres are in Howard County and 374.5 acres are in Glasscock County; then

- 6 -

West at 1407.7 varas pass a large stone G. Co. No. 9; and at 1559 varas a set stone on the East edge of highway No. 9; and at 1569.5 cross the West line of Survey 7 in Block 32, Township 2-South, Texas & Pacific Railway Company, at a point 468 varas South 14[°] 34' East of its N. W. corner, which shows of Survey 7, 39.4 acres are in Howard County and 72.1 acres are in Glasscock County; and at 1600.3 varas a large set stone on the West bank of draw marked, N line Glasscock Co.; and at 1622 varas a concrete pier marked, 14, on top, under East field fence, with clear glass bottle buried on the South side, from which a mesquite nine inches bears North 34[°] 09' East 22 varas, and a windmill North 30[°] 45' West; and at 1900.8 varas a point for mile post No. 14 in a field.

0

<u>Mile 15.</u> THENCE West at 453.4 varas pass a set stone half mile G. Co.; and at 1407.7 pass a set stone marked, G. Co. 10 W; and at 1557.8 varas cross the South line of Survey No. 5, Block 32, at a point 69.5 varas North 75° 41' East of its original S. W. corner; and at 1629 varas cross the West line of Survey 5, Block 32, at a point 17.5 varas North 14° 34' West of its original S. W. corner being a set stone marked, N. W. VIII, which shows of Survey No. 5, 1/10 of one acre is in Glasscock County, and of Survey 8, Block 32, 75.8 acres are in Howard County and 564.2 acres are in Glasscock County; and at 1900.8 varas a concrete pier mile post 15, marked as before described, with 15 on top, from which a five inch mesquite bears South 60° 41' West 69 varas, and windmill South 25° 09' West and a DO South 9° 58' East.

Mile 16. THENCE West at 456 varas pass half G. Co. milepost marked CLK; and at 1407.7 varas pass a stone mound marked, 11 W K; and at 1693.7 varas a stone mound in the West line of Survey 13 on the East side of a North and South road 502.2 varas North 14[°] 34' West from two-inch iron pipe marked, S W 13 - S E 14 - N E 23 - N W 24 - M. O. Co., the S. W. cor-

Counter 55144

6

- 7 -

ner of Survey 13, which shows of Survey 13, 87.7 acres are in Glasscock County and 552.3 acres are in Howard County; then West at 1900.8 varas a concrete pier marked as before described, the 16th mile, from whence a five inch mesquite bears North 77° 17' East 51 varas; B on flat rock North 31° 40' East 27.5 varas; water tower at Stanton North 81° West.

0

0

0

<u>Mile 17.</u> THENCE West at 453 varas pass a stone half mile G. Co. line; at 1407 varas the 12th mile on Glasscock County, set stone; and at 1751.6 varas cross the West line of Survey 14, and fence line, 986.9 varas North 14[°] 14[°] West of the S.W. corner of Survey 14, which shows that 392.5 acres of Survey 14 are in H₀ ward County and 251.5 acres are in Glasscock County; and in all 1900.8 varas a concrete monument, marked as above described, for the seventeenth mile of Howard County.

<u>Mile 18.</u> THENCE West at 453 varas pass a half mile stone G. Co. marked, C L; and at 1407 varas pass a stone 6" x 18" x 30" marked, C L 13 W K, from which an old set stone and rock mound marked, 13 W, bears South 13.4 varas; and West at 1825 varas the center line of Garden City and Big Spring graded highway which is the West line of Survey 15, at a point 443 varas South 15[°] East of a fence corner on West side of highway near the N. W. corner of Survey 15, which shows of Survey 15, 230.1 acres are in Howard County and 413.9 acres are in Elasscock County; then west at 1833.09 varas a stone on the West side of highway marked, Glasscock Co. line; and in all 1900.8 varas to a concrete pier, marked as above described, with a triangle on the West side, for the eighteenth mile.

Mile 19. THENCE West at 1406.6 varas pass a stone 2 x 7 x 12 marked, 14 W, which is about 60 varas S. E. of M. M. Edwards ranch house; and at 1890.8 cross fence, the West line of Survey 9, which shows of Survey 9, 5/10 of one acre in Glasscock

- 8 -

County; and of Survey 16, 68.2 acres are in Howard County and 573.8 acres are in Glasscock County; and in all 1900.8 varas to a concrete pier marked as before described, with 19 on top face, for the 19th mile.

0

0

0

<u>Mile 20.</u> THENCE West at 413.3 varas a point in North and South fence from which the center of an ornamental steeple on Cox's farm house bears North 27° 15' West about 300 varas, said fence being along the East side of a field; and West 1250 varas pass the West side of field; and at 1410 varas a set stone, the fifteenth G. Co. mile, which is 14 varas North of an old pile of stone, one small stone marked, 15 W; at 1900.8 varas, a point in a field, for the twentieth mile, from which a concrete pier marked as before described, with 20 + marked on top, under a North and South fence bears West varas.

<u>Mile 21.</u> THENCE West crossing the W_est line of Survey 8 at 246 cross a North and South fence and concrete pier about 105 varas S. E. of McFarland farm house; said fence is near the West line of Survey 8, which shows 99.6 acres are in Glasscock County and 545.4 acres are in Howard County of Survey 8; then West at 1900.8 varas to a set stone for the twentyfirst mile.

Mile 22. THENCE West at 117 varas cross North and South fence on the East side of graded highway, a concrete pier marked as before described, with 21 + on top for reference point; and at

varas cross the West line of Survey 7 which is the center of said North and South graded road at a point South 15° 09: East 865.7 varas from a square stone set in the center line of said highway, being the N. W. corner of Survey 7, which shows of Survey 7, 373.4 acres are in Howard County and 266.6 acres are in Glasscock County; then West at 1900.8 varas to a concrete pier marked as before described, with 22 on top face, set on the East slope of a sandy ridge, from which a windmill at Aleufian Ranch headquarters bears South 21° 18' West and

- 9 -

counter 35146 mil miles or hannes

another windmill bears South 53° 54' West, and a 4 inch mesquite in a clump of mesquites marked, K, bears South 66° East 52.4 varas.

0

0

0

Counter 55/47 mable of human

<u>Mile 23.</u> THENCE West crossing the West line of Survey 12, Block 34, Township 2-South, at a point 321 varas South 15° 07[•] East of its N. W. corner, which shows of Survey 12, 199.8 acres are in Howard County and 444.2 acres are in Glasscock County; then West at 600 varas the East edge of Mustang draw; and at 1406 varas a set stone, the eighteenth G. Co. milestone; and in all 1900.8 varas to a concrete pier marked as before described, with 23 on top face, from which the water tower at Stanton bears North 76[°] 13[•] West, and a set stone under East and West fence bears South 55[°] 13[•] West 271.7 varas.

Mile 24. THENCE West crossing the West line of Survey 2 at a point 180.9 varas North 15[°] West of its S. W. corner, which shows of Survey 2, 9.7 acres are in Glasscock County and 634.3 acres are in Howard County; and of Survey 11, 29.2 acres are in Howard County and 610.8 acres are in Glasscock County; then West at 1402 varas a set stone marked, 19 W; and at 1900.8 varas a concrete pier, mile post 24, on the East side of a sandy ridge from which a windmill bears South 36[°] 43st East, and a DO bears North 48[°] 21st 30st East, and a four inch mesquite bears South 39[°] 52st East, marked K, 23.2 varas.

Mile 25. THENCE West crossing the West line of Survey 3 at a point 1197.2 varas South 15[°] 04' East of its N. W. corner, which shows of Survey 3, 491 acres are in Howard County and 149 acres are in Glasscock County; then West at 1005 varas cross a road course N. W.; and at 1900.8 varas a concrete pier in brushy flat marked, 25 W on top, from which a windmill bears North 5[°] East and a DO Morth 26[°] West, and a three inch mesquite in a clump of four bears South 9[°] 53' East 99.2 varas marked, XXV.

Mile 26. THENCE West at 401 varas cross a fence the West line of

- 10 -

Survey 4 at a point 712.5 varas South 14⁰ 56' East from its N. W. corner, which shows of Survey 4, 321.5 acres are in Howard County and 322.5 acres are in Glasscock County; thence West at 1041 varas cross a fence; and at 1359 cross a road; and at 1400 a set stone marked, G. Co. 21 K, on South side, and H C B on North face, which is 10.5 varas North of an earth mound and four pits, as described by T. H. Seay on this line; and at 1900.8 varas a concrete pier, marked as before described, with 26 on top face.

0

0

C.

<u>Mile 27.</u> THENCE West at 468.7 varas cross a North and South fence, the West line of Survey 5, at a point 210 varas South 15[°] 15' East of a bois d'arc stake at fence corner, the N. W. corner of Survey 5, which shows 155.3 acres of Survey 5 in Howard County and 484.7 acres are in Glasscock County; thence West at 1288.5 varas cross the North line of Survey 6, Block 34, Township 2-South, which is the South line of Survey 43, Block 34, Township 1-South, at a point 786.7 varas South 75[°] 15' West of the N. E. corner of Survey 6, which shows of Survey 6, 14.6 acres are in Howard County and 625.4 acres are in Glasscock County; thence West at 1900.8 varas a point in a sandy field for milepost 27.

Mile 28. THENCE West at 105 varas set a concrete pier marked as above described under a North and South field fence; and at 522.5 varas cross a North and South fence; and at 534.3 cross the West line of Survey 43 at a point 293.2 varas North 14° 44' West of its original S. W. corner, which is marked by an eight-inch cedar stake, a stone mound, and a two-inch galvanized iron pipe marked, 48 - 43 - 1 - 6 - M. O. Co., which shows of Survey 43, 611.1 acres are in Howard County and 28.9 acres are in Glasscock County; thence West at 1407 varas pass a set stone, G. Co. 23 K on South side, from which an old earth mound and trench, barely visible, Seay & Clift's monument, bears South 7 varas, and an eight-inch mesquite marked, B, South 8° 03' West

- 11 -

29.8 varas, water tower at Stanton North 68° 38' West; then West at 1900.8 varas a concrete pier marked, 28, on top, from which the point of a mountain North 50° 40' East, and water tower at Stanton North 67° 56' West.

0

0

0

0,

<u>Mile 29.</u> THENCE West at 577.5 varas cross a North and South fence the West line of Survey 48, 1103.6 varas South 15° 04' East of its N. W. corner, which shows of Survey 48, 456.6 acres are in Howard County and 183.4 acres are in Glasscock County; thence West at 1400 varas pass a set stone marked, G. Co. 24 K; and at 1900.8 varas a conceste pier marked on top face, 29, otherwise marked as before described, from which a four inch mesquite bears North 34° 24' East 73.5 varas, and a windmill bears North 59° 45' East, and a DO North 89° 48' East.

Mile 30. THENCE West crossing West line of Survey 47 at a point 603 varas South 14° 54' East from its N. W. corner, which shows 287 acres in Howard County and 353 acres in Glasscock County; and at 1407.7 varas pass a stone marked, G. Co. 25 K, at the N. W. end of Lake Petite, from which an old stone mound by Clift & Seay bears South 5 varas; and at 1900.8 varas a concrete pier marked, Glasscock, on the South side, and S. W. Cor. Howard Co., on Northf ace, and 30 on top face, and an eight inch cedar post, from which a four-inch mesquite marked, B, bears North 39° 51' West 20.1 varas; and the South one of twin mesquites marked, K, South 78° 03' East 118.5 varas, and a distant windmill South 70° 54' East, and a DO South 26° 39' West about 900 varas, which is the S. W. corner of Howard County and the S. E. corner of Martin County, Texas.

- 12 -

Counter 55149 100

Bearings marked B and K., as well as other marks in calls of the foregoing field notes.

0

Surveyed May 14th to June 16th, 1928, inclusive.

0

0

John Woody \$ J.C. Alsup, \$

Chain Carriers.

0

We, R.T. Bucy. Surveyor for Howard County and W.F. Kellis, Surveyor for Sterling and Glasscock Counties, Texas, do hereby certify that the foregoing described Survey was actually made by us on the ground, according to law, on the date and with the Chain Carriers aforesaid, duly qualified, and that all the corners, lines, boundaries and marks of the same, whether natural or artificial, are truly and correctly described and set forth in the foregoing Plat and Field Notes.

Witness our hands and seals at Sterling City, Texas, this the 16th day of July, 1928.

-13-

Surveyor for Howard County.

Cellis

Surveyor for Sterling and Glasscock Counties.

NOTE A.

0

0

0

0

The Field Notes, as recited above, are made in obedience to an order of the Honorable County Courts of Howard, Sterling and Glasscock Counties, of the day of

, A. D. 1928, for said boundary line to be established on the ground; and we hereby complete same and return for record and file the above notes.

NOTE B.

The above line was determined by accepting the position of a monument, placed formerly by surveyors in locating certain county boundaries, at the S. W. corner of Mitchell County and the S. E. corner of Howard County, and another monument at the N. E. corner of Glasscock and the N. W. corner of Sterling County. These two monuments are on this line; however, a parallel of latitude passing through either one of these monuments, the other one would be off of that parallel a distance of 33.6 varas. Therefore we tied these two monuments, being in distance 9004.4 varas apart; and we tied the same and placed the boundary as hereinabove described as a tangent between these points. And at milepost No. 6 on the South line of Howard County, and also at mileposts 12, 18, 24 and 30 on the South line of Howard County an angle of 3 minutes was turned, and the monuments between these posts were set on six mile chords of latitude; and the courses recited hereinabove are compared to a true meridian on Polaris, both in extreme elongation with an Azimuth angle of 1° 16' 30" and Polaris at upper culmination.

And as determined at several places along this line, the magnetic declination was found to be from North 10° 52' East to North 12° 15' East.

Surveyed May and June, 1928.

- 14-

Counter 55151

Licensed Land Surveyors of Texas.

0

NOTE A.

The Field Notes, as recited above, are made in obedience to an order of the Honorable County Courts of Howard, Sterling and Glasscock Counties, of the day of

, A. D. 1928, for said boundary line to be established on the ground; and we hereby complete same and return for record and file the above notes.

NOTE B.

The above line was determined by accepting the position of a monument, placed formerly by surveyors in locating certain county boundaries, at the 5. W. corner of Mitchell County and the S. E. corner of Howard County, and another monument at the N. E. corner of Classcock and the N. W. corner of Sterling County. These two monuments are on this line; however, a parallel of latitude passing through either one of these monopants, the other one would be off of thet parallel a distance of 33.6 verter ind county. County Creck, monuments, Define to the distance of distance of the other of the county.

Witness my hand and official seal, at office in Sterling City, Texas, this the 17th. day of July, A.D. 1928.

County of Sterling. \$ I, D.C.Durham, County Clerk of Sterling County, Texas, hereby certify that the Toregoing fifteen (15) pages, contains a true and correct copy of the Field Notes of a Survey of the South Line of Howard County and Portions of the North Line of Sterling and Glasscock Counties, State of Texas, as prepared by R.T.Bucy and W.F.Kellis, Licensed Land Surveyors of the State of Texas, filed in my office on the 17th. day of July, A.D. 1928, as same appears of record in the Minutes of the County Court of Sterling County, Texas, in Volume 2, page 114, et seq.

ar Inconstante of Lexade ameridian on Polaris, both in extreme

alongation with an Azimuth angle of 1 16. 30" and Polaris at upper culmination.

And as determined at several places along this line, the magnetic declination was found to be from North 10° 52' East to North 12° 15' East.

Surveyed May and June, 1928.

Howard co Bdry. Tim #3

Licensed Land Surveyors of Texas.

THE STATE OF TEXAS) COUNTY OF GLASSCOCK) I, Joe C. Calverley, County Clerk, of Glasscock County, Texas, do hereby certify that the foregoing fifteen (15) pages contains a true and correct copy of the Field Notes of a Survey of the South Line of Howard County, and Portions of the North Line of Sterling and Glasscock Counties, State of Texas, as prepared by R.T.Bucy and W.F.Kellis, Licensed Land Surveyors of the State of Texas, filed in my office on the 17th day of July, A.D. 1928, as same appears of record in the Minutes of the County Court of Glasscock County, Texas, in Volume 1, page 167, et seq.

Witness my hand and official seal, at office in Garden City, Texas, this the 17th day of July, A. D. 1928.

Joe C. Calverley By Marke athley Deputy.

Howwal 20. Bduy. Will # 3

The State of Texas, County of Howard. (I,J.I.Prichard, County Clerk, of Howard County, Texas, do hereby certify that the foregoing 15 pages contain a true and correct copy of the Field notes of survey of the South Line of Howard County, and portions of the north line of Sterling and Glasscock Counties, State of Texas, as prepeared by R.T.Bucy and W.F.Kellis, Licensed Land Surveyors of the State of Texas, filed in my office on the 16th day of July, A.D.1928 at 5:30 P.M. as same appears of record in County Court Minutes, of Howard County, Texas.Vol.No.2-Page 552 et seq. Given under my hand and seal of office, this 19th.day of July A.D.1928.

County Clerk Howard County Texas.

Howard Co. Bdry line, South hime Howard and Month lines Glasscocker and Storling Coz Filed July 20th 1928 J.T. Robison, Cour. Examined as approved august 17th 1928 appears to be a retrace of the line between Howard and Glasscoke Countries run by T.H./ Szay 38 W= Cliff in 1906_/ 0 16 Pageson Counter 55.154