

REPORT OF SURVEY NORTH BOUNDARY
HUTCHINSON COUNTY, TEXAS.

STATE OF TEXAS,)
)
COUNTY OF HUTCHINSON.)

TO THE HONORABLE COUNTY COURT OF HUTCHINSON COUNTY:

In compliance with your Order to establish and mark the North Boundary of Hutchinson County, I, T. O. James, a licensed State Land Surveyor, was at the Southwest corner Hansford County at 1 o'clock P. M. Dec. 5th, 1928, that being the place and time designated in your Order.

I there met Mr. R. G. Armstrong, representing your County. D. B. Stribling, of Roberts County, was also present.

Mr. Armstrong and I not agreeing as to the correctness of this corner, as already established, for the common corner of Hutchinson, Hansford, Moore and Sherman Counties, we referred the matter to the Commissioner of the General Land Office by a night-letter. The Comr. requested a detailed statement of our disagreement, signed by each of us.

I could not find Mr. Armstrong to prepare and file such statement, but very soon thereafter he filed with your Court a report purporting to be a survey of the 4 corners of Hutchinson County, accepting the 2 North corners as correct.

On March 2nd, 1929, it was agreed between Officials of Hutchinson and Hansford Counties that I proceed, alone, to establish and mark the Boundary in compliance with said Order, allotting the acreage in each section, crossed by said boundary, to the proper county.

Beginning on the 14th day of March, I therefore ran a preliminary line from the recognized Southwest corner of Hansford County Eastward 30 miles to a concrete cone set by W. D. Twichell in 1907 for the Northwest corner of Roberts County and found the cone to be in excess of 30 miles.

To determine more accurately its proper location I awaited the survey of the Boundary of Ochiltree and Hansford Counties, the same having been ordered by the County Courts of said Counties.

In this survey, assisted by Allen of Ochiltree County and Stribling of Roberts County, from the Northeast corner of Hansford County, in the North line of the State of Texas, the same being a rock marked O 30 on east side and H on west, we ran a true Meridian South, with two

sets of chain carriers, and found this cement cone to be 30 miles 1311.5 varas. As this was a greater excess than we deemed correct, it was agreed that we measure the East line of Lipscomb County for comparison. This I did, Aug. 14th, to 19th, with one set of chain-carriers, and found the said line to be 30 miles 1271.1 vrs.

Reporting said finding to the above named surveyors, we met the 29th day of Aug. and made a new, reinforce concrete pillar for the correct corner of Hutchinson, Hansford, Ochiltree and Roberts Counties. 40.4 varas North of the one existing.

Following the establishment of the Southeast corner of Hansford County, Northeast corner of Hutchinson County, I proceeded to make the survey, the accompanying fieldnotes of which are a full description.

Respectfully submitted,

(Seal)

T. O. James,

Licensed State Land Surveyor.

STATE OF TEXAS,)
)
COUNTY OF HUTCHINSON.)

FIELD NOTES to a survey of the Boundary line between Hansford and Hutchinson Counties, Texas, the same being the South line of Hansford County and the North line of Hutchinson County.

Beginning at a 2" pipe, 2 feet high, marked N. E. Moore, S. E. Sherman for the S. W. corner of Hansford County and the N. W. corner of Hutchinson County and from which the 29th mile, in the boundary of Hansford and Sherman counties bears North 1 mile 1156 varas; and the 30th mile in said boundary bears North 0° 1' E. 1042 vrs. Also the 29th mile (no 30th mile being found) in the boundary line of Sherman and Moore counties beras N. 89° 59' 30" W. 1 mile 446.5 varas. The North line of survey 38, Block 3, G. H. and H. RR. Co. bears South 364 vrs. Thence East 950 vrs. a pipe set in the east line of survey 35, 1" Mi. said Block 3, 1900.8 vrs. a 2" pipe marked 1 H 29 H set in ground 4 pits and a mound of earth, 2 ft high, for the 1st mile; Thence East 810 vrs. a fence under which is set a 1½" pipe, 1900.8 vrs. a 2" pipe, 30" long, marked 2 H 28 H set in ground, 2nd Mi. 4 pits and an earth mound, 2 ft. high, for the 2nd mile;

Thence East 885. vrs. a fence under which is set a $1\frac{1}{2}$ " pipe,
 3rd. Mi. 1900.8 vrs. a 2" pipe, 50" long, marked 3 H 27 H set in ground,
 a circular trench and a mound of earth, 2 ft. high, for the 3rd mile;
 Thence East 1345 vrs. a fence under which is set a $1\frac{1}{2}$ " pipe,
 1600 vrs. pass north edge of lake basin, 1900.8 vrs. a 2" pipe
 4th. Mi. marked 4 H 26 H set in ground, 4 pits and a mound of earth 2 Ft.
 high, for the 4th Mile and from which a Bois de arc post beras north
 281 vrs. W. 2.1 vrs;
 Thence East 900 vrs. a draw, 1440 vrs. a draw, 1900.8 vrs. a 2"
 5th Mi. pipe 30" long, marked 5 H 25H set in ground, 4 pits and an earth
 mound, 2 ft. high, for the 5th mile;
 Thence East 1700 vrs. a draw, 1900.8 vrs. a 2" pipe, 30" long,
 6th Mi. marked 6 H 24 H set in ground, 4 pits and an earth mound, 2 ft.
 high, for the 6th mile;
 Thence East 1150 vrs. a draw, 1584 vrs. a draw, 1900.8 vrs. a 2"
 7th Mi. pipe 30" long, marked 7 H 23 H Set in ground, 4 pits and an earth
 mound, 2 ft. high, for the 7th mile and from which a Boie de arc
 post bears north 284 vrs/;
 Thence East 42 vrs. a fence under which is set a $1\frac{1}{2}$ " pipe,
 and from which the center of Highway is South 386 vrs, 252 vrs.
 a draw, 950.4 vrs. an angle of $0^{\circ} \overset{9'}{.26}$ " is taken for correction of
 8th Mi. Latitude, approximately 36° N. Lat. (all mile stations are set off
 the property distance for correction of Tangent) 1900.8 vrs a
 2" pipe, 30" long, marked 8H 22 H set in ground, a circular trench
 and mound of earth, 2 ft. high, for the 8th mile;
 Thence East 47 vrs. a pipe set in center of a road, 780 vrs. cross
 the C R I and P RR. 1900.8 vrs. a 2" pipe, 30" long, marked 9 H
 9th Mi. 21 H set in ground, 4 pits and a mound of earth for the 9th mile
 and from which the S E corner of section 30, block 5 T, in center
 of cross roads, beras South 392 vrs. East 50 vrs.
 Thence East, cross road, 61 vrs. to a fence under which is set
 10th Mi. a $1\frac{1}{2}$ " pipe, 447 vrs. cross South Fork of Palo Duro, 1900.8 vrs.
 a 2" pipe, 30" long, marked 10 H 20 H set in ground, 4 pits and
 mound of earth, 2 ft. high, for the 10th mile;
 Thence East 38 vrs. a fence under which a $1\frac{1}{2}$ " pipe, 48 vrs. cross
 highway, 1900.8 vrs. a 2" pipe, 30" long, marked 11 H 19 H set in
 11th. ground, 4 pits and a mound of earth, 2 Ft. high, for the 11th mile

from which a Bois de arc post beras North 301 vrs. West 7
vrs:

Thence East 1103 vrs. a fence under which is set a $1\frac{1}{2}$ " pipe,
12th Mi. 1224 vrs. a drain bearing S. W. 1900.8 vrs. a 2" pipe, 30"
long, marked 12 H 18 H set in ground, 4 pits and mound of
earth, 2 ft. high 12^{mi}.

Thence East 1438 vrs. a fence under which is set a $1\frac{1}{2}$ "
pipe, from which a pipe set for the N. W. corner of survey 22,
13th. Mi. S. A. and M. G, bears North 1366.4 vrs. 1900.8 vrs. a 2" pipe,
30" long, marked 13 H 17 H set in ground, a circular trench
and mound of earth, 2 ft. high, for the 13th mile:

Thence East 1461 vrs a fence under which is set a $1\frac{1}{2}$ " pipe,
14th Mi. 1900.8 vrs. a 2" pipe, 30" long, marked 14 H 16 H set in
ground, a circular trench and mound of earth, 2 ft. high
for the 14th mile:

Thence East 1353 vrs. a draw leading to a lake about a $\frac{1}{2}$
mile north 1457 vrs. a fence under which is met a $1\frac{1}{2}$ " pipe
15th Mi. 1900.8 vrs. a 2" pipe, 30" long, marked 15 H 15 H set in
ground, 4 pits and mound of earth 2 ft. high, for the 15th
mile:

Thence East 1472 vrs. a fence under which is set a $1\frac{1}{2}$ "
pipe, from which the S. E. corner of survey 192, Block
16th Mi. 45, H and T. C. Beras North 1440 vrs, 1900.8 vrs. a 2"
pipe, 30" long, marked 16 H 14H set in ground, a circular
trench and a mound of earth, 2 ft. high, for the 16th mile;
Thence East 1477 vrs. a fence under which a $1\frac{1}{2}$ " pipe is set,
17th Mi. 1900.8 vrs. a 2" pipe, 30" long, marked 17 H 13 H set in
ground, 4 pits and a mound of earth, 2 ft. high, for the
17th mile;

Thence East 349 vrs. cross Horse Creek, brg. N. E. 1485
vrs. a pipe set in center of road on east line of survey 18,
18th Mi. 1900.8 vrs. a 2" pipe, 30" long, marked 18 H 12 H set in
ground, a circular trench and a mound of earth, 2 ft high,
for the 18th mile:

Thence East 1515 vrs, a fence under which a $1\frac{1}{2}$ " pipe is set,
1900.8^{vrs} a 2" pipe, 30" long, marked 19 H 11 H Set in ground,
19th Mi. a trench and a mound of earth, 2 ft. high, for the 19th mile;

Thence East 958 vrs a fence west side of orchard under which is set a $1\frac{1}{4}$ " pipe, 1160 a drain to a large lake basin N E 1493 vrs. a fence and $1\frac{1}{4}$ " pipe, from which the S E corner of survey 16, S A and M G, bears South 392 vrs East 10.8 vrs.

20th Mi. 1900.8 vrs a 2" pipe, 30" long, marked 20 H 10 H set in ground, 4 pits and a mound of earth, 2 Ft. high, for 20th mile and from which a Bois de arc post bears North 370.7 vrs. East 7 vrs.;

Thence East 324 vrs to 497 vrs a dry lake, 1503 vrs a $1\frac{1}{4}$ " pipe set, 1900.8 vrs a 2" pipe, 30" long, marked 21 H 9 H set in ground, a circular trench and mound of earth, 2 ft. high, for the 21st mile;

Thence East 1503 vrs a $1\frac{1}{4}$ " pipe set, 1900.8 vrs a 2" pipe, 30" long, marked 22 H 8 H set in ground, a circular trench and a mound of earth, 2 ft. high, for the 22nd mile;

Thence East 950.4 vrs, an angle of $0^{\circ} 9' 26''$ is taken for correction of Latitude (approximately 36° N. Lat.) 1900.8 vrs a 2" pipe, 30" long, marked 23 H 7 H set in ground, a circular trench and a mound of earth, 2 ft high, for the 23rd mile;

Thence East 1494 vrs a fence under which is set a $1\frac{1}{4}$ " pipe, 1900.8 vrs a 2" pipe, 30" long, marked 24 H 6 H set in ground, a circular trench and a mound of earth, 2 ft high, for the 24th mile;

Thence Esat 1567 vrs a fence under which a $1\frac{1}{4}$ " pipe is set, 1900.8 vrs a 2" pipe, 30" long, marked 25 H 5 H set in ground, a circular trench and a mound of earth, 2 ft. high, for the 25th mile;

Thence East, thru an orchard, 1584 vrs a fence under which is set a $1\frac{1}{4}$ " pipe, 1900.8 vrs a 2" pipe marked 26 H 4 H set in ground, a circular trench and a mound of earth, 2 ft high for 26th mile;

Thence East 1631 vrs a fence under which is set a $1\frac{1}{4}$ " pipe, 1900.8 vrs. a 2" pipe, 30" long, marked 27 H 3 H set in ground, a circular trench and a mound of earth, 2 ft. high, for the 27th mile;

Thence East 1571 vrs a fence under which is set a $1\frac{1}{4}$ " pipe,

1900.8 vrs a 2" pipe, 30" long, marked 28 H 2 H set in ground,
28th Mi. a circular trench and mound of earth 2 ft. high, for the
28th mile;

Thence East 1571 vrs from which point a pipe set for the S E
corner of survey 57, Block R. bears South 167 vrs. 1900.8
29th Mi. vrs a 2" pipe 30" long, marked 29 H 1 H set in ground, 4 pits
and a mound of earth, 2 ft high, for the 29th mile and from
which a Bois de arc post bears North 457 vrs East 38 vrs;

Thence East 1575.7 vrs a fence under which a 1 1/2" pipe is set
and and from which a pipe is South 143 vrs, set for the SW
30th Mi. corner survey 55, Block R, 2075.7 vrs a concrete pillar, 14
inch base, 6 inch top 5 ft. long is set 2 1/2 ft in the ground
for the S E corner Hansford County and the N E corner Hutchin-
son County and from which a concrete cone bears South 40.4 vrs;

Surveyed March 14 to 16,	Paul Beeson - - - -) Chain
April 1 to 5 ,	Rex Cochran - - - -) Carriers
Aug. 26 to 29,		
Sept. 5 to 18, 1929.		

I, T. O. James, licensed State Land Surveyor, in and for the State
of Texas, do hereby certify that the foregoing described survey was made by me
on the ground and that the corners, lines, boundaries and marks of the same are
truly described in the foregoing Fieldnotes.

(Seal)

T. O. James,

Licensed State Land Surveyor.

Filed with the County Court of Hutchinson County, this 20th day of Sept, 1930.

Ona Bryan, County Clerk,

(Seal)

By Eltha L. Edgar, Deputy.

I, H. M. Hood, Judge of the County Court of Hutchinson County,
Texas, have this day examined and approved the above and foregoing "Report of
Survey of the North Line of Hutchinson County, Texas, as reported and filed
by T. O. James, Licensed State Land Surveyor.

Dated at Stinnett, Texas, this the 20th day of Sept. A. D. 1930.

(Seal)

H. M. Hood, County Judge.

THE STATE OF TEXAS,)
)
COUNTY OF HUTCHINSON.)

I, ONA BRYAN, Clerk of the County Court in and for Hutchinson County, Texas, do hereby certify that the above and foregoing is a true and correct copy of Report of Survey of the North Line Hutchinson County, Texas, as same appears on file in my office.

Given under my hand and official seal in office at Stinnett, Texas, this the 23rd day of Sept. A. D. 1930.

Ona Bryan, County Clerk,
in and for Hutchinson County, Texas.

By *Edna Plummer* Deputy.

Hansford-Hutchinson
County Line

Hutchinson Co. Bdry
(6)

Filed March 11th 1931

J. H. Walker, Court-
Clerk

Abstracted in
Vol. 54, Apr. 28, 1931

750

Counter 55312

D58