SEP 3 0 1940 G<mark>eneral Land Office</mark> 198

FIELD NOTES of a survey of the line between Potter and Randall Counties.

made by E. McBride and W. J. Williams, by virtue of order of the County Court of Potter County and notice to the County Court of Randall County, setting February 23, 1931, as the date to begin the survey, to which the county Court responded by appointing W. J. Williams to represent Randall County by order made February 14, 1931.

The surveyors met at the time and place designated and proceeded to retract and re-mark the line between Potter and Rendall Counties, conforming with the line marked by W. D. Twichell, special surveyor for Potter and Randall Counties, made in the year 1898.

The positions and areas of sections in Block 2, A. B. & M. are considered to be where now held, indicated by fences and centers of public roads as these locations will likely remain as they are now held by virtue of limitation, acquiescence, agreement or other reasons which will constitute estoppel.

The positions and areas of sections in Block 9, B. S. & F. conform with resurvey of Block 9, made by state surveyor, W. D. Twichell. Section No. 4, Block 5 Z and sections 32, 33 and 34, Block 8, crossed by the west end of the line between the counties are considered to be where now held and defined by fences and centers of public roads and areas are so computed.

Beginning at a frustrum of square pyramid of concrete, 5 feet high, 24 inches square at bottom and 12 inches square at top, set 30 inches in ground and in center of top of which is a 5 inch bronze disc marked POTTER COUNTY RANDALL COUNTY ARMSTRONG COUNTY CARSON COUNTY and being 7406 feet South of mile 59. (4 old pits) made by W. D. Twichell on the east line of Potter County, and on the parallel of latitude passing through remaining evidences of the south line of Potter as surveyed by Twichell and above referred to.

Thence West at 3900.2 feet (1404.1 varas) a concrete post 6"x6"x36" set in ground about 30 inches, with a 3" bronze disc set in middle of top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 0. 7386 set under fence between sections 9 and 14, Block 2, A. B. & M;

Thence West at about 30 feet cross the West line of Section No. 9 and 1757.8 feet from a brick set in ground and claimed as its southwest corner, in all 5282.4 feet (1901.7 varas) to a concrete post 6"x6"x36" set in ground about 30 inches deep with 3 inch bronze disc on top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 1.7391, being 4 feet east of fence on east side of lane between sections 14 and 31, Block 2, A. B. & M;

Thence West at 34 feet, middle of lane, the west line of Section No. 14, Block 2, in all 5278.5 feet (1900.3 varas) to a concrete post 6"x6"x 36" set in ground about 30 inches with 3" bronze disc set in middle of top and marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 2.7388.

Thence West at 1.5 feet cross fence between sections 31 and 36, Block 2, at 5371 feet (1933 varas) a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 3.7561 set under fence between sections 36 and 53, Block 2, and 1735.5 feet north from middle of public road along their south line;

Randall Co Bdry Line 6

Survey of Potter-Randall County line--- # 2

Thence West at 1280 feet pass remains of zinc cone in lake basin, Twichell's 4th mile from southeast corner of Potter County, in all 5245 feet (1888.2 varas) concrete post 6"x6"x36" with bronze disc 3 inches in diameter marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 4.7494 in middle of top set in ground 30 inches deep under fence;

Thence West at 28 feet middle of public road between sections 53 and 58 Block 2, in all 5248 feet (1889.3 varas) to a concrete post 6"x6"x36" with a 3" bronze disc set in middle of top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 5.7434 set in ground about 30 inches, under fence;

Thence West at 40 feet middle of public road between sections 58 and 75, Block 2, in all 5313 feet (1912.7 varas) to a concrete post 6"x6"x36" with 3 inch bronze disc on top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 6.7496 set in ground about 30 inches deep under fence;

Thence West at 27 feet middle of public road between sections 75 and 90, Block 2, in all 5293feet (1905.5 varas) to a concrete post 6"x6"x36" with 3" bronze disc set in middle of top and marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 7.7521 set in ground about 30 inches under fence;

Thence West crossing public road 5274 feet (1898.6 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 8.7509 set in ground about 30 inches under fence;

Thence West at 30 feet middle of public road between sections 107 and 122, Block 2, and 1805.9 feet north of middle of public road along their south line, at 60.5 feet pass 35.9 feet south from southeast corner of tract No. 1, Block 4 of Famous Heights Addition to Amarillo, at 1309 feet pass 2 old pits, Twichell's 9th mile from the southeast corner of Potter County, in all 5277 feet (1899.7 varas) to a concrete post 6"x6"x36" with bronze disc 3 inches in diameter marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 9.7504 in top set in ground 30 inches deep under fence from which the northwest corner of tract No. 5, Block 8, Famous Heights Addition bears south 28.1 feet and the southwest corner of tract No. 5, Block 9 bears north 31.9 feet;

Thence West at 33 feet middle of public road on east line of Section No. 139, Block 2, and 1707.9 feet north of middle of public road on its south line, in all 5312.3 feet (1912.3 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M/ P. 10.7565 set in ground about 30 inches under fence;

about 30 inches under fence; Thence West at about 30 feet middle of public road between sections 139 and 154, Block 2 and 1680.6 feet north of public road on their south line, at 77 feet the southeast corner of Lot 6, Block 196 of Glenwood Addition to Amarillo bears north 29.7 feet, at 4130 feet the southeast corner of Lot No. 6, Block 37, Glenwood bears north 21.8 feet and the northeast corner of cemetery bears south 38.2 feet, at 5295.3 feet the southwest corner of Lot No. 7, Block 9, Glenwood bears north 18.9 feet, at 7610.1 feet the northeast corner of lot No. 10, Block 63, Eakle Addition bears north 237 feet, at 7896.4 feet the northeast corner of Lot No. 10, Block 131 Eakle Addition bears south 99.1 feet, at 10626.4 feet Survey of Potter-Randall County line --- # 3

the northeast corner of lot No. 1, Block 30, Wolflin Place Addition to Amarillo bears north 216.6 feet, at 11716.4 feet the northeast corner of Lot No. 1, Block 23, Wolflin Place bears north 213.7 feet and the southeast corner of Lot No. 10, bears south 386.3 feet at 12206.4 feet cross the west line of Lot No. 4, Block 22, Wolflin Place 27.6 feet from southwest corner, in all 15846.7 feet (5704.8 varas) to a concrete post 6"x 6"x36" with a 3" bronze disc set in middle of top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 13.7578 set in ground about 30 inches, under fence;

Thence West at 30 feet middle of public road between sections 186 and 227, Block 2, in all 5311.5 feet (1912.1 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 14.7637 set in ground about 30 inches under fence;

Thence West at 29 feet middle of public road between sections &27 Block 2 and 1757.1 feet north of a 2 inch pipe for its southwest corner and No. 8, Block 9 at 2466.8 feet from middle of public road on its south line, in all 5469.7 feet (1969.1 varas) to a concrete post 6"x6"x 36" with bronze disc 3 inches in diameter marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 15.7997 in top set in ground 30 inches deep under fence;

Thence West at 35 feet middle of public road between section 8 and 27, Block 9, at 2438.3 north of middle of public road on their south line, in all 5384 feet (1938.2 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 16.8195 set in ground about 30 inches under fence;

Thence West at 30 feet middle of public road between sections 27 and 42 Block 9, in all 5377 feet (1935.7 varas) to a concrete post 6"x6"x36" with 3 inch bronze disc on top marked POTTER COUNTY RANDALL COUNTY M. P. 17.8379 set in ground about 30 inches under fence:

Thence West at 30 feet middle of public road between sections 42 and 61, Block 9, in all 5382.1 feet (1937.6 varas) to a concrete post 6"x6"x36" with 3" bronze disc set in middle of top and marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 18.8570 set in ground about 30 inches under fence;

Thence West at 22 feet middle of public road between sections 61 and 76, Block 9, in all 5379.8 feet (1936.7 varas) to a concrete post 6"x6" x36" with a 3" bronze disc set in middle of top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 19.8756 set in ground about 30 inches, under fence;

Thence West at 34 feet middle of public road between sections 76 and 95 Block 9, in all 5378 feet (1936.1 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 20.8945 set in ground about 30 inches under fence;

Thence West at 31.5 feet from middle of public road between sections 95 and 110, Block 9, in all 5365 feet (1931.4 varas) to a concrete post 6"x6"x36" with bronze disc 3 inches in diameter marked POTTER COUNTY RANDALL COUNTY 1930. M. P. 21.9106 in top set in ground 30 inches deep under fence;

RL

Survey of Potter-Randall County line --- # 4

Thence West at 30 feet middle of public road between sections 110 and 129, Block 9, in all 5405 feet (1945.5 varas) to a concrete post 6"x6"x 36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 22.9333 set in ground about 30 inches under fence;

Thence West 5344 feet (1923.8 varas) to a concrete post 6"x6"x36" with 3" bronze disc set in top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 23.9454 set in ground about 30 inches under fence;

Thence West at 30 feet middle of public road between sections 144 and 163, Block 9, 2288 feet north of southwest corner of Section No. 144 in all 5280.8 feet (1901.1 varas) to a concrete post 6"x6"x36" with 3" bronze disc set in top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 24.9456 set in ground about 30 inches under fence;

Thence West at 30 feet middle of public road between sections 163 and 178, Block 9, in all 7012.8 feet (2524.6 varas) to a concrete post 6"x6"x36" with 3 inch bronze disc on top marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 26.2147 set in ground about 30 inches under fence;

Thence West 3549.6 feet (1277.9 varas) to a concrete post 6"x6"x36" with 3" bronze disc set in middle of top and marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 26.9460 set in ground about 30 inches;

Thence West at 30 feet middle of public road between sections 197, Block 9, and 4, Block 5 Z, and 3083.6 feet south of stone for northwest corner of No. 197, in all 4557.7 feet (1640.8 varas) to a concrete post 6"x6"x36" with a 3" bronze disc set in middle of top marked POTTER C CUNTY RANDALL COUNTY 1930 M. P. 27.8292 set in ground about 30 inches under fence in old pit, remains of 3rd mile on Twichell's south line of Potter County:

Thence West at 30 feet middle of public road between sections 4, Block 5 Z and 32, Block 8, 2140.6 feet south of stone the northwest corner of Section No. 4, Block 5 Z, in all 5298.6 feet (1907.5 varas) to a concrete post 6"x6"x36" marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 28.8138 set in ground about 30 inches under fence between sections 32 and 33, Block 8;

Thence West 5299.4 feet (1907.8 varas) to a concrete post 6"x6"x36" with bronze disc 3 inches in diameter marked POTTER COUNTY RANDALL COUNTY 1930 M. P. 29.8174 in top set in ground 30 inches deep under west fence of lane between sections 32⁴ and 33, Block 8 from which 3 old pits, the remains of Twichell's 1st milepost from southwest Potter, bear east 58 feet;

Thence West 5226.6 feet (1881.6 varas) to a frustrum of square pyramid of concrete 24 inches at bottom and 12 inches at top and 60 inches high set in ground 30 unches under west fence of Section No. 35, Block 8 at place occupied by 2 old stones and traces of old pits north and south the remains of Twichell's southwest corner of Potter County. A 5 inch bronze disc marked POTTER COUNTY RANDALL COUNTY DEAF SMITH COUNTY OLDHAM COUNTY set in middle of top of monument.

- 0 - 0 - 0 - 0 - 0 -

R3

Survey of Potter-Randall County line --- # 5

We, E. McBride, Special Surveyor for Potter County and W. J. Williams, Special Surveyor for Randall County, by virtue of orders issued by the County Court of Potter County dated January 29th A. D. 1931 and by the County Court of Randall County dated February 14th A. D. 1931 do hereby certify that the foregoing survey was made by us on the ground according to the orders above cited and that the corners, boundaries and areas are correctly described and set forth in the foregoing plat and field notes, recorded in Book ---- Page--- County Court Records of Potter County and in Book "BOUNDARIES" Page 1 to 14 of the County Court Records of Randall County.

Witness our hands this 20th day of March, A. D. 1931.

W. J. Williams, Special Surveyor for Randall County and Licensed Land Surveyor of Texas.

E. McBride, Special Surveyor for Potter County...

- 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 -

LANYON, TEXAS

The undersigned hereby certifies that the foregoing, consisting of 5 pages, including this sheet or page, constitutes a full, true and complete copy of the instrument shown. This 27th day of September, A. D., 1940.

> GUARANTY ABSTRACT & TITLE CO. Inc Canyon, Texas.

Justeni Mgr ... By M

courts 58149

R4

Randall Co Born & Line 6 CIERT. OPY F/N. NORTH LINE RANDALL CO SOUTH LINE POTTER CO 134 N.O. WILLIAMS AND S. ME BRIDE SURVEY BRENNING FEB 23-1931 10-40 58150 Minist Mi Williame, eW Williame, eM Md Vd bewel At the foregoing survey was made by us on the groun are above cited and that the corners boundaries by described and and that for the torners, boundaries orded in Bount are Page --- County Court Hecords of Book "BOUNDARIES" Page 1 to lt of the County Court ounty. an you , TITE CO. · · . A d185 Mar. Sis