

Roberts Co. Boundary
North, West + South lines
Roberts Co filed June 18/99

For E. line see Hemphill W. line
approved 9/12/94

2
Approved 8/23/99

Roberts Co Bdry Line 2b

[Faint, illegible handwriting]

The State of Texas }
Roberts County } Field-notes of
a survey of the North, West and
South Boundary lines of Roberts
County Texas, done by order of the
Commissioners Court of said County issued
on the 14th. day of March A.D. 1899

May 15th. 1899 Var. used $10^{\circ}30' E$.
Beginning at an Iron pipe set in stone
pile two feet high, said pipe marked 30, m.
and is on N.W. line of survey No. 30 Block
43 A & J. C. Ray Co. Survey the same
being the North-West Corner of Hemphill
County

Thence West at 2000 vrs descend rocky bluff
at 585 vrs. pass cedar post set in ground at 791
vrs. cross wire fence at 900 vrs. cross a creek (S.E.)
at 1550 cross draw (S.E.) at 1900 vrs. set an
Iron pipe 2' x 4 ft. marked R. 1. O. 29.

Thence West, from above pipe, at 1000 vrs. descend
a rocky bluff at 1600 vrs. cross a creek (S.), at
1820 vrs. cross a creek (S.E.) at 1840 recross same
creek (S.W.) at 1900 vrs. set an Iron pipe 2' x 4 ft.
marked R. 2. O. 28.

Thence West from above pipe, at 80 vrs. recross
same creek (S.) at 704 vrs. ascend rock bluff at
1420 vrs. descend rock bluff at 1880 vrs. cross
creek (S.W.) at 1900 vrs. set an Iron pipe 2' x 4 ft.
marked R. 3. O. 27

Roberts Co. Bd'y. Linc # 25
4 3
Thence West, from above pipe, at 2000 vs. cross
same creek (nw.) at 900 vs. recross same (S.E.)
at 220^{vs}, cross long draw (S.E.) at 910 vs. ascend
a rock bluff at 1780 vs. Cross a Cañon (S.E.) at
1900 vs. set an Iron pipe ^{2'x4ft} marked R. 4. O. 26

3
Thence West, from above pipe, at 1000 vs. cross a
dup short cañon (nw.) at 1640 vs. cross very
deep cañon (S.) at 1860 ascend rock bluff at
1900 vs. set an Iron pipe 2'x4 ft. Marked R. 5. O. 25
said pipe is on top of high rocky point

6
Thence West, from above pipe, at 2000 vs. descend
rock bluff at 340 vs. Cross a creek (S.E.) at
700 vs. ascend rock bluff at 1860 vs. descend
a rock bluff at 1900 vs. set an Iron pipe
marked R. 6. O. 24

May 16th 1899

Begin at above described pipe

7
Thence West at 140 vs. cross creek (S.) at 240
ascend a rock bluff at 1600 vs. descend a
rock bluff at 1900 vs. set an Iron pipe
2'x4 ft. marked R. 7. O. 23

8
Thence West from above pipe, at 260 vs. cross
creek (S.) at 800 vs. ascend rock bluff at 1900
vs. set an Iron pipe 2'x4 ft. marked R. 8. O. 22
same is on high ridge and 13 vs. West from a
wagon road

Thence West, from above pipe, at 600 vs. cross

a deep cañon (S.W.) at 1710 vs. cross cañon (S.) at 1900 vs. set an Iron pipe 2' x 4 ft. marked R. 9. O. 21 same is in small draw (E)

Thence West, from above pipe, at 800 vs. cross deep cañon (S.) at 1900 vs. set an Iron pipe 2' x 4 ft. marked R. 10. O. 20

Thence West from above pipe, at 600 vs. cross deep cañon (S.) at 1900 vs. set an Iron pipe 2' x 4 ft. marked R. 11. O. 19 same is on level flat

Thence West, from above pipe, at 1140 cross a very deep cañon (S.) at 1900 vs. set an Iron pipe, marked R. 12. O. 18

Thence West, from above pipe, at 1900 vs. set an Iron pipe marked R. 13. O. 17 same is on smooth level flat

Thence West, from above pipe, at 560 vs. cross deep cañon (S.E.) at 1900 vs. set an Iron pipe, marked R. 14. O. 16. same is on a level prairie.

May 17th, 1899

Begin at the above described pipe marked R. 14. O. 16

Thence West at 320 vs. cross cañon (S.W.)

at 980 vs. cross cañon (S.E.) at 1430 vs

cross wire fence at 1630 vs. pass 363 vs.

North from the N.E. corner of survey No. 160

Block 13 G. & N.O. Rwy, Co. Surveys at 1900 vs

set an Iron pipe, marked R. 15. O. 15 - same is

on a smooth flat at head of small draw (S.)

(3)

Roberts Co. Bdry. Lin #26

Thence West, from above pipe, at 1600 vrs. cross small cañon (s.w.) at 1900^{vrs.} set an Iron pipe 2'x4 ft. marked R. 16. O. 14 same is on high rocky point (16)

Thence West, ^{from above pipe} at 580 vrs. cross deep cañon (s.) at 1600 vrs. cross deep cañon (s.e.) at 1900 vrs. set an Iron pipe 2'x4 ft. marked R. 17. O. 13 same is on East face of Hill (17)

Thence West, from above pipe, 1900 vrs. set an Iron pipe 2'x4 ft. marked R. 18. O. 12 same is on West face of a Hill. (18)

May 18th 1899

Begin at above pipe marked R. 18. O. 12
Thence West, ^{from above pipe} at 200 vrs. cross deep cañon (s.) at 900 vrs. cross deep cañon (s.e.) at 1900 vrs. set an Iron pipe 2'x4 ft. R. 19. O. 11 same is in deep cañon (s.) (19)

Thence West, from above pipe, at 390 vrs. a high divide at 790 vrs. cross deep cañon (s.e.) at 1900 vrs. set an Iron pipe 2'x4 ft. marked R. 20. O. 10 in a deep cañon (s.) (20)

Thence West, from above pipe, crossing two deep cañons (s.) 1900 vrs. set an Iron pipe 2'x4 ft. marked R. 21. O. 9 same is on ^{North face} side of bluff at foot of cliff (21)

Thence West, from above pipe, at 1190 vrs. cross head of a draw (s.e.) at 1900 vrs. set an Iron pipe 2'x4 ft. marked R. 22. O. 8 on East slope of smooth prairie (22)

May 19 - 1899

Begin at above pipe marked R. 22. O. 8

23 } Thence West at 1400 vrs. cross deep cañon (S.W.)
at 1900 vrs. set an Iron pipe 2' x 4 ft. marked
R. 23. O. 7. same is in a deep cañon (S.E.)

24 } Thence West, from above pipe, at 1040 vrs.
enter cañon (S.) at 1740 leave same at 1900
set an Iron pipe 2' x 4 ft. marked R. 24. O. 6.
same is on North face of hill and 1000 vrs. south
from a deep cañon

25 } Thence West, from above pipe, at 520 vrs. cross
head of a cañon (S.W.) at 1200 vrs. descend
a rock bluff at 1900 vrs. set an Iron pipe
2' x 4 ft. marked R. 25. O. 5.

24 } Thence West, from above pipe, at 280 vrs. cross
a creek (S.) at 1020 vrs. ascend a rock bluff at 1400
vrs. cross a deep cañon (S.) at 1800 vrs. cross deep
cañon (S.E.) at 1900 vrs. set an Iron pipe 2' x 4 ft.
marked R. 26. O. 4. 1000 vrs. South from a deep cañon

27 } Thence West, from above pipe, at 800 vrs. cross
cañon (S.W.) at 1675 vrs. cross deep cañon (S.E.)
at 1900 vrs. set an Iron pipe 2' x 4 ft. marked
R. 27. O. 3. and 20 vrs. South from a pond

28 } Thence West, from above pipe, 1900 vrs. set
an Iron pipe 2' x 4 ft. marked R. 28. O. 2 on
smooth level prairie

5 } Thence West, from above pipe, 1900 vrs. set Iron pipe
2' x 4 ft. marked ~~27~~ R. 29. O. 1. on level plains

May 20th, 1899

Begin at above pipe marked R. 29. O. 1

Thence West at 774 vrs. Cross a wire fence at

1900 vrs. set an Iron pipe 2' x 4 ft. marked

N.W. N.E. S.E. S.W.

R. H. H. O. for the N.W. corner of Roberts

County, same is on level plains, from which pipe

a round knob with cedars on top vrs. S. 77° E. and

another vrs. S. 8° E. and center of bank of small

cañon vrs. S. 28° W. about 500 vrs.

A Thence South, from above pipe at 1300 vrs. cross

head of a deep cañon (S.E.) at 1725 vrs. descend

bluff into same cañon (S.W.) at 1900 vrs. set an

Iron pipe 2' x 4 ft. marked R. 1. H. 29 at East foot

of high bluff

Thence South, from above pipe, 1900 vrs. set an

Iron pipe 2' x 4 ft. marked R. 2. H. 28. on sandy

ridge about midway between foot of bluff and

creek and about 200 vrs. from each

Thence South, from above pipe, at 220 vrs. cross

said creek (S.W.) at 820 vrs. recross same (S.E.) at

1900 vrs. set an Iron pipe 2' x 4 ft. marked R. 3. H. 27

Thence South, from above pipe, at 500 vrs. cross creek

(S.E.) at 1900 set an Iron pipe 2' x 4 ft. marked

R. 4. H. 26.

Thence South, from above pipe, at 300 vrs. cross

creek (S.E.) at 1900 vrs. set an Iron pipe, 2' x 4 ft.

marked R. 5. H. 25, on East face of a hill

1
Thence South, from above pipe, across a broken ridge 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 6. H. 24., on East face of hill

16
Thence South, from above pipe, 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 7. H. 23., on a sage brush flat.

17
Thence South, from above pipe, 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 8. H. 22., on top of a sand hill

18
Thence South, from above pipe, at 360 vs. bluff of Canadian river at 1580 vs. old North bank of river at 1804 vs. cross wire fence at 1866 vs. present North bank of river set an Iron pipe 2' x 4 ft. marked R. H. at 1900 vs. point in river bed.

May 22nd. 1899

19
Beginning at the above described point in bed of Canadian river

20
Thence South at 955 vs. South bank of said river at 1273 vs. pass 435 vs. East from N.E. corner of Survey No. 30 Block 46 Ft. & G. C. Rwy. Co. Surveys at 1540 vs. cross slough (E) at 1860 vs. cross slough (E) at 1900 vs. set an Iron pipe 2' x 4 ft. marked R. 10. H. 20

21
Thence South from above pipe, at 120 vs. cross a slough (E) at 690 vs. foot of sand hills at 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 11. H. 19., on North face of a hill

12
Thence South, from above pipe, 1900 vrs. set an
Iron pipe, 2' x 4 ft. marked R. 12, H. 18, on south
face of sand hill.

13
Thence South, from above pipe, at 805 vrs. cross
wire fence at 1900 vrs. set an Iron pipe, 2' x 4 ft.
marked R. 13, H. 17, on south face of sand hill.

May 23rd, 1899

Beginning at the above described pipe marked R. 13, H. 17

14
Thence South 1900 vrs. set an Iron pipe, 2' x 4 ft.
marked R. 14, H. 16, on small flat in sand hills

15
Thence South, from above pipe, 1900 vrs. set an
Iron pipe, 2' x 4 ft. marked R. 15, H. 15, on south
face of sand hill and 20 vrs. west from a wire fence

16
Thence South, from above pipe, at 180 vrs. cross
said wire fence, at 1900 vrs. set an Iron pipe
2' x 4 ft. marked R. 16, H. 14

17
Thence South, from above pipe, 1900 vrs. set
an Iron pipe, 2' x 4 ft. marked R. 17, H. 13, in
small mesquite flat.

18
Thence South, from above pipe, at 130 vrs. cross
Timber Creek (N.W.), about 80 vrs. East from its
junction with West Timber Creek, at 256 vrs. pass
215 vrs. East from an Iron pipe marked 181, 206. the
supposed N.W. corner of Survey No. 181 Block 2
D & G. N. Remy Co. Survey, at 270 vrs. cross wire fence
in bed of W. Timber Cr. at 420 vrs. cross W. Timber
Creek (N.W.) at 1120 vrs. recross same (N.W.) at 1360 vrs.

enter same Cr. (N.W.) at 1800 leave same (on West side)
at 1900 vrs. set an Iron pipe, 2' x 4 ft. marked
R. 18. H. 12., 600 vrs. West from creek.

Thence South from above pipe, at 1400 vrs. Cross
N. Timber creek (N.E.) at 700 vrs. Cross long draw
(N.W.) at 1860 vrs. recross same (N.E.) at 1900 vrs.
set an Iron pipe 2' x 4 ft. marked R. 19. H. 11., on
flat 20 vrs. East from branch

Thence South, from above pipe, at 30 vrs. Cross
same draw (N.W.) at 1900 vrs. set an Iron pipe,
2' x 4 ft. marked R. 20. H. 10., on South face of a hill

Thence South, from above pipe, at 380 vrs. Cross
a long draw (N.E.) at 1900 vrs. set an Iron pipe,
2' x 4 ft. marked R. 21. H. 9., on smooth prairie
between two long flat draws

Thence South, from above pipe, 1900 vrs. set
an Iron pipe, 2' x 4 ft. marked R. 22. H. 8., at the
head of a short Cañon (N.W.)

Thence South, from above pipe, at 320 vrs.
Cross Cañon (N.) at 1140 vrs. Cross Cañon (N.)
at 1900 vrs. set an Iron pipe, 2' x 4 ft. marked
R. 23. H. 7., on South slope of hill.

Thence South, from above pipe, at 360 vrs. Cross
Cañon (N.) at 1460 vrs. Cross Cañon (N.W.) at 1900 vrs
set an Iron pipe, 2' x 4 ft. marked R. 24. H. 6.,
on top of high ridge

Thence South, from above pipe, at 560 vrs. Cross
draw (S.W.) at 720 vrs. Cross draw (N.W.) at 1900

Roberts Co. Bdry. Cont #28

vs, set an Iron pipe 2' x 4 ft. marked R. 25, H. 5, on level mesquite flat.

Thence South, from above pipe, at 400 vs. Cross West Timber Creek (N.W.) at 1550 vs. Cross draw (N.E.) at 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 26, H. 4, on smooth prairie

May 24th, 1899

Beginning at the above described pipe marked R. 26, H. 4.

Thence South at 530 vs. Cross wagon road at 1880 vs. Cross Cañon (S.W.) at 1900 set an Iron pipe, 2' x 4 ft. marked R. 27, H. 3, on North face of a hill.

Thence South, from above pipe, at 1820 vs. Cross Cañon (W.) at 1900 vs. set an Iron pipe, 2' x 4 ft. marked R. 28, H. 2, on North slope of Hill

Thence South, from above pipe, at 660 vs. Cross a branch (N.W.) at 1295 vs. descend rocky bluff at 1720 vs. Cross branch (S.W.) at 1900 vs. set an Iron pipe 2' x 4 ft. marked R. 29, H. 1.

Thence South (from the above pipe) at 220 vs. Cross East prong of White Deer Creek (N.W.) at 560 vs. ascend a bluff at 1300 vs. Cross deep draw (N.W.)

at 1900 set an Iron pipe, 2' x 4 ft. marked S.W. S.E. N.E. N.W.

R. H. C. Co., for S.W. corner of Roberts

County, said pipe is on south face of a hill, and from which pipe a lone cedar on a high point bro.

N. 2° W. a Hackberry in a Cañon bro. N. 23° W and a

Cluster of Hackberry trees on creek br. N. 23 $\frac{3}{4}$ W.
a lone tree in Cañon br. N. 53 $\frac{3}{4}$ E. and a round
Knoll br. N. 52 $\frac{3}{4}$ E.

1 Thence East, from above described pipe, at 170
vrs. Cross draw (N.) at 850 vrs. Cross draw (N.) at
1160 vrs. Cross Cañon (N.) at 1884 vrs. Cross
East prong of White Deer creek ^(N.W.) at 1900 vrs. set
an Iron pipe, 2' x 4 ft. marked R. 1. G. 29., at the
foot of bluff bank of creek.

2 Thence East, from above pipe, at 79 vrs. recross
same creek (S.W.) at 350 vrs. recross same creek
(N.W.) at 1800 vrs. Cross a draw at its junction
with another (S.W.) at 1900 vrs. set an Iron pipe,
2' x 4 ft. marked R. 2. G. 28.,

3 Thence East, from above pipe, at 1070 vrs. cross
draw (S.W.) at 1478 vrs. Cross draw (S.W.) at 1900
vrs. set an Iron pipe 2' x 4 ft. marked R. 3. G. 27.

4 Thence East from above pipe, at 1774 vrs. pass
209 vrs. North from an Iron pipe marked ^{141, 142-120, 121} B. 2 B3
at 1900 vrs. set an Iron pipe 2' x 4 ft. marked
R. 4. G. 26.

5 Thence East from above pipe, at 576 vrs. cross
draw (S.E.) at 645 vrs. recross same (S.E.) at 1055
vrs. recross same (S.E.) at 1190 vrs. recross same
(N.E.) at 1826 vrs. cross wire fence 188 $\frac{1}{2}$ vrs. North
^{97, 116, 120, 141} from an Iron pipe marked B2 B3 at 1900 vrs.

(11) Thence East from above pipe, at 445 vrs. cross
draw (S.E.) at 645 vrs. recross same (S.E.) at 1055
vrs. recross same (S.E.) at 1190 vrs. recross same
(N.E.) at 1826 vrs. cross wire fence 188 $\frac{1}{2}$ vrs. North
^{97, 116, 120, 141} from an Iron pipe marked B2 B3 at 1900 vrs.
set an Iron pipe 2' x 4 ft. marked R. 5. G. 25.

Thence East, from above pipe, at 445 vrs. cross

Draw (N.E.) at 1900 set an Iron pipe, 2'x4 ft marked R. 6, G. 24, on North slope of smooth prairie

7 Thence East, from above pipe, at 1174 vs. Cross branch (S.E.) at 1900^{vs} set an Iron pipe, 2'x4 ft. marked R. 7, G. 23, on level plains

8 Thence East, from above pipe, 1900 vs. set an Iron pipe 2'x4 ft. marked R. 8, G. 22,

9 Thence East, from above pipe, at 592 vs. Cross draw (S.E.) at 1552 vs. Cross branch (S.E.) at 1900 vs. set an Iron pipe 2'x4 ft. marked R. 9, G. 21.

10 Thence East, from above pipe, at 112 vs. Cross draw (S.W.) at 1900 vs. set an Iron pipe 2'x4 ft. marked R. 10, G. 20.

May 26th - 1899 Thence East, from above pipe, 1900 vs. set an Iron pipe 2'x4 ft. marked R. 11, G. 19.

11 Thence East, from above pipe, 1900 vs. set an Iron pipe 2'x4 ft. marked R. 12, G. 18.

12 Thence East, from above pipe, at 988 vs. Cross branch (S.) at 1900 vs. set an Iron pipe, 2'x4 ft. marked R. 13, G. 17, on East slope of a hill.

14 Thence East from above pipe at 316 vs. pass 28 vs. South from an Iron pipe marked ^{1.24-13.37} B. 3 B. 2. at 675 vs. Cross draw (S.E.) at 1317 vs. Cross draw (S.) at 1900 vs. set an Iron pipe, 2'x4 ft. marked R. 14, G. 16, on East slope of a hill

15

Thence East, from above pipe, at 110 vrs.
Cross draw (S.E.) at 286 vrs. Cross wire fence
at 926 vrs. Cross deep creek (S.E.) at 1900 vrs
set an Iron pipe, 2' x 4 ft. marked R. 15, G. 15.
in a farm

16

Thence East, from above pipe, at 200 vrs.
Cross creek (S.E.) at 535 vrs. Cross A. T.
& S. T. Rail Road at 715 vrs. Cross old
channel of creek (N.W.) at 785 vrs. Cross Red
Deer Creek (N.E.) at 1900 vrs. set an Iron
pipe 2' x 4 ft. marked R. 16, G. 14.

17

Thence East, from above pipe, at 648 vrs.
pass 20 vrs. North from an Iron pipe marked
205, 206, 187, 188
B.M. 2 at 1700 vrs. Cross deep draw (N.W.)
at 1900 vrs. set an Iron pipe ^{2' x 4 ft.} marked
R. 17, G. 13, on south slope of hill

18

Thence East, from above pipe, at 1130 vrs
Cross cañon (N.) at 1900 vrs. set an Iron
pipe, 2' x 4 ft. marked R. 18, G. 12, on west
slope of hill

19

Thence East, from above pipe, at 626 vrs Cross
deep cañon (N.) at 822 vrs. Cross wire fence
at 1100 vrs. Cross a deep cañon (N.W.) at 1900
vrs. set an Iron pipe 2' x 4 ft. marked
R. 19, G. 11.

(13)

20

Thence East, from above pipe, at 45 vrs. Cross
short draw (N.W.) at 675 vrs. Cross draw (N.E.) at
790 vrs. pass 77 vrs. South from an Iron pipe

Roberts Co. Bldg. Linn #26

153, 154, 140, 139

marked: B.M. 2. at 1600 vrs. Cross a
cañon (N.E.) at 1775 vrs. Cross cañon (N.W.)
at 1900 vrs. set an Iron pipe 2' x 4 ft.
marked R. 20, G. 10,

21 Thence East, from above pipe, at 295 vrs. Cross
draw (N.W.) at 980 vrs. Cross branch (N.E.) at
1900 vrs. set an Iron pipe 2' x 4 ft. marked
R. 21, G. 9., on East slope of hill

22 Thence East, from above pipe, at 581 vrs. Cross
cañon (N.E.) at 623 vrs. Cross cañon (N.) at
825 vrs. Cross cañon (N.) at 1900 vrs. set an
Iron pipe 2' x 4 ft. marked R. 22, G. 8., on
east slope of hill

23 Thence East, from above pipe, at 82 vrs. Cross
cañon (N.) at 350 vrs. Cross cañon (N.E.) at 1900
vrs. set an Iron pipe, 2' x 4 ft. marked
R. 23, G. 7., same is in a farm on level
plains

May 27-1899

24 Thence East, from above pipe, 1900
vrs. set an Iron pipe 1 3/4' x 4 ft. marked
R. 24, G. 6., 10 vrs. North from a small draw

25 Thence East, from above pipe, 1900 vrs.
set an Iron pipe 1 3/4' x 4 ft. marked
R. 25, G. 5., on level plains

26 Thence East, from above pipe, 1900 vrs.
set an Iron pipe 2' x 4 ft. marked
R. 26, G. 4., 20 vrs. S.W. from a small draw

27 Thence East, from above pipe, 1900 vrs.
set an Iron pipe $1\frac{3}{4}' \times 4$ ft. marked
R. 27. G. 3, on level plains

28 Thence East, from above pipe, 1900 vrs.
set an Iron pipe $1\frac{3}{4}' \times 4$ ft. marked
R. 28. G. 2, on level plains

29 Thence East, from above pipe, 1900 vrs.
set an Iron pipe $1\frac{3}{4}' \times 4$ ft. marked
R. 29. G. 1, on level plains

30 Thence East, from above pipe, 1900 vrs.
a dressed stone set in ground under a
wire fence said stone marked S.W. H. on N.E.
face and S.E. R. Co. on N.W. face the same be-
ing the S.W. corner of Humphill Co.
and S.E. corner of Roberts County,

Surveyed May 15th to May 27th, 1899

Walter Kelly } Chain
Frank Kelly } Carriers

J. W. P. Hedgecock, County Surveyor
of Roberts County do hereby Certify
that the foregoing survey was actually
made by me on the ground on the dates
and with the Chain carriers aforesaid duly
qualified, and that the same was done strictly
according to law and in conformity with
the rules relative to the curvature of the

Roberts Co. Bdry. Line #26

of the earth, and that the marks of the same ~~are~~ natural and artificial are truly described and set forth in the foregoing field-notes, and that they are recorded in Vol. 3 Pages 196 to 204 Surveyors Records of Roberts County,

W. P. Hedgecock

County Surveyor

Roberts County

Texas

I, W. P. Hedgecock County Surveyor Roberts County, do hereby certify, that on the 15th day of May 1899 at 9 o'clock A.M. I began the foregoing survey at the N.W. corner of Hempick County as per order of the Court and that there was no one present to represent Ochiltree County and that no one appeared in that capacity at any time thereafter while the survey was being made

W. P. Hedgecock

County Surveyor

Roberts Co. Tex.

8

1985 58361

Roberts Co 3 Extra Line 26

North, West + South
line 5 Roberts Co.

Filed in General Land
Office June 18th 1899

L. C. Wise

Approved after
letter of Explanation
(see letter) 8/23/99
L. C. Wise

file, but does not de-
scribe the corners of A.
with reference to Survey.
This does not enable the
office to know whether
surveyor in surveying at
S.W. Cor. of Memphis Co.
found the same corner
described by Cunningham
& Ford in 1894 a corner
stone 12" x 12" x 24", the S.W.
Cor. Survey 13 pl. A. 2.
No corner is described at
N.E. Cor. with reference
to survey - The N.E. Cor.
of 160 pl. 13 and N.W. Cor.
of Sur. 44 pl. 43 by field
notes have common corner
while surveyor in plat

of North line which
survey shows the
survey over half
mile apart - This
requires explanation

The surveyor may
not require new
notes - but let him
send in small sketch
showing position of
survey at corners
of ~~the~~ what he
found at S.W. Cor
Memphis Co. and
make explanation
required - This of-
fice can then
approve or reject
his notes
L. C. Wise
6/24/99

A



No. 1477

Ordered that N. P. Hedgecock County Surveyor proceed on the 15th day of May, 1899, to the N.E. Corner of Roberts County and begin the establishing of the following lines to wit; Lines between Roberts County and Ochiltree County, line between Roberts County and Hutchins County, line between Roberts County and Gray County. The said N. P. Hedgecock to furnish all material and pay all expenses of said work.

The same to be done in accordance with law and after the above described work has been done and approved by the Commissioner of the General Land Office at Austin Texas, then the said N. P. Hedgecock is to receive \$350.00 for same.

State of Texas?
County of Roberts / I J Isaac Williams County Clerk in and for County and State aforesaid do hereby certify that the foregoing is a true copy of the Order on the Minutes of the Commissioners Court passed on the 14th day of March 1899
Witness my hand and seal of Office this 6th day of June 1899.

J Isaac Williams
County Clerk Roberts Co Texas.