Sterling County. South Boundary Gent Land Office August 16 1907,

At a regular term of the Commissioners Court of Sterling County, Texas, which began on May 13,1907, the County Judge and all members thereof being present, the following order was made and passed, to-wit:

.

Ordered by the Court that the Field notes and Map made by J.E. Beavers and W.F.Kellis, establishing by survey the South boundary line of Sterling County, be and the same are hereby accepted and approved, and the Clerk is hereby instructed to record the same in the Minutes of this Court and to make certified copy of said Map and Field notes and forward to the General Land Office at Austin Texas.

THE STATE OF TEXAS # COUNTIES OF STERLING & TOM GREEN # April 18, 1907. Magnetic Variation from Polaris 10⁰ 10' East. Bearings Marked:

Field Notes of a Survey of the South Boundary Line of Sterling County, Made by Virtue of an order of the County Courts of Sterling and Tom Green Counties, Made on the day of 1907.

Beginning at a stone monument marked "N. L. T. G. Co." on the South face, "S. W. Cor. C. Co." on N. face, and "March 17, 1891" on top, the same being the S. W. Cor. of Coke County, and the most Northern S. E. Cor. of Sterling County, in the N. line of Tom Green County, from which

Golgotha Mountain brs. N. 45° W.;

Haystack Hill brs. S. 87-3/4° E.;

The N. W. Cor. of Sur. No. 1, H. E. & W. T. Ry. Co., Cert. No. 1143 brs. N. 14^o W. 1055 vrs.

1st MILE.

Thence N. 73° 45' W. through a mesquite flat:

at 264 vrs. cross line of Sur. No. 1, H. E. & W. T. Ry. Co. and Sur. No. 3, # T. C. Ry. Co., at a point 956 vrs. S. of their N. Common Corner;

At 1900 vrs. set stone monument 20" x 12" x 6" marked "C. L. No. 1" set in mound of stones, from which

A mesquite 6" dia. brs. S. 17-1/2° W. 15 vrs.;

A three-pronged mesquite brs. N. 47-3/40 E. 18 vrs.

2nd MILE.

Thence N. 73° 45' W.

At 360 vrs. cross line between Surs. Nos. 3 & 4, T. C. Ry. Co. at a point 502 vrs. S. of their N. Common Corner; Corner found and identified, which is a mound ofsstone, from which

The West end of a hill brs. N. 9° W.

Point of hill brs. N. 82-1/2° W.;

At 1180 vrs. S. end of spur of hill; At 1900 vrs. set stone monument 3-1/2' x 16" x 4" marked "C. L. No. 2"

28

Sterling Co Bary Line

set in mound of stone, from which Mesquite 5" dia. brs. S. 27-1/4° E. 64 vrs.; Mesquite 8" dia. brs. N. 44° E. 8 vrs.

3d MILE.

Thence North 730 45' West:

At 78 vrs. cross N. lone of Sur. No. 4, T. C. Ry. Co. and S. line of Ann Morrison Sur. No. 6, Cert. No. 28/75;

At 383 vrs.the S. E. Cor. of Sur. No. 33, Block 11, S. P. Ry. Co., which is a stone mound, found and identified by being 1916-3/4 vrs. E. from the S. W. Cor. of said Sur. No. 33, which is a mound of

stone, from which

A mesquite stump brs. N. 41° W. 33 vrs.

A mesquite stump brs. East 114 vrs.;

set a stone monument 5-1/2' x l' x 10" marked "MID S E COR S. Co." on N. W. face, "N. W. Cor. T. G. Co. S. E. Cor. 33", on S. E.

face, from which

Mesquite 8" dia. brs. S. 67-1/4° W. 102-3/4 vrs.;

A mesquite 8" dia. brs. N. 58-1/2 W. 88-1/2 vrs.;

A peak brs. S. 59° West;

North end of rocky ledge brs. East;

N. E. Cor. of Sur. No. 7 brs. S. 29-3/4° W. 134 vrs.;

Said monument being the S. E. Re-entering Corner of Sterling County,

and N. W. Cor. of Tom Green County.

IST MILE South from S. E. Cor.Sterling Co. Thence South 3' East:

At 116-3/10 vrs. pass 66-1/2 vrs. E. of the N. W. Cor. of Sur. No. 4, T. C. Ry. Co., said Cor. found and identified, which is a mound of

stone, from which

West end of hill brs. N. 85° E.;

Rocky point brs. N. 27º W.;

At 933 vrs. creek S. E.;

At 1620 vrs. set stone monument 30" x 20" x 3" marked "C. L. 9", set in mound of stone, from which

36

A mesquite 7" dia. brs. S. 22-1/2° E. 6 vrs.;

A mesquite 6" dia. brs. N. 15° E. 15 vrs.;

A peak brs. N. 36-1/2º East.

Courte 58922

2ND MILE.

Thence S. 3' East through mesquite flat:

At 425 vrs. pass 25-6/10 vrs. E. of the N. W. Cor. of Sur. No. 5, G. C. & S. F.;

At 877 vrs. a draw, course S. E.;

At 1900 vrs. set stone monument 30" x 24" x 4" marked "C. L. 8" from which A mesquite 8" dia brs. S. 55-1/2° W. 36-1/2 vrs.; A mesquite 7" dia. brs. N. 11-1/5° W. 21 vrs.

3D MILE.

Thence South 3' East:

At 451 vrs. pass 14 vrs. W. of the S. W. Cor. of Sur. No. 5, G. C. &

S. F. Ry. Co., which is a mound of stone, from which

Monon Hill brs. N. 79-3/4° W.;

A peak brs. N. 17-3/4° West;

At 656 vrs. Mulberry Creek, course N. E.;

At 1810 vrs. cross N. line of Sur. No. 82, Block No. 5, H. & T. C. Ry. Co., at a point 31 vrs. E. of the N. W. Cor. of said Sur. 82; At 1900 vrs. set stone monument 30" x 24" x 8" marked "C. L. 7" in

mound of stone, from which

A mesquite 5" dia. brs. S. $6-1/4^{\circ}$ W. 11-3/4 vrs.; A mesquite 8" dia. brs. N. 21° E. 52 vrs.

4TH MILE.

Thence 3' East:

At 1300 vrs. cross draw, course N. W.;

At 1820 vrs. fence;

AT 1850 vrs. cross Sterling Creek and San Angelo Road, Brs. East & West; At 1900 vrs. set stone monument 4' x 1' x 3" marked "C. L. 6" in mound

of stones on N. slope of hill, from which

A mesquite 5" dia. brs. N. 2-1/2° E. 10 vrs.;

A mesquite 3" dia. brs. N. 89° W. 20 vrs.;

N. W. Cor. of Sur. No. 80, Block No. 5, H. & T. C. Ry. Co., brs. N. 82 vrs. and West 1919 vrs., the same being a stone mound, found and identified.

Thence South 3' East over rocky hill and scattering meaquite: At 730 vrs. tol of spur ofhill;

At 1048 vrs. draw N. W.;

At 1280 vrs. top of ridge, N. E. & S. W.;

At 1832 vrs. pass 46 vrs. E. of N. W. Cor. of Sur. No. 72, Block 5,

H. &. T. C. Ry. Co.; a stone mound, found and identified;

At 1900 vrs. set stone monument 4' x 2' x 5", marked "C. L. 5" set in mound of stone, from which

A mesquite 6" dia. Brs. S. 67-1/4° W. 47 vrs.g

A mesquite 6" dia. brs. N. 8° E. 42 vrs. same being on East slope of hill in head of a draw.

6TH MILE.

Thence South 3' Bast:

At 800 vrs. top of rocky ridge, S. E. & N. W.;

At 1844 vrs. pass 34 vrs. E. of the N. W. Cor. of Sur. No. 69, Block

5, H. & T. C. Ry. Co.;

At 1900 vrs. set stone monument 3' x 1-1/2' x 4" marked "C. L. 4" in mound of stone, from which

Windmill bra. S. 72-1/2º West;

A hackberry mott brs. S. 150 West, this Cor. being in head of draw, cause ##### S. W.

7TH MILE.

Thence South, 3' East:

At 960 vrs. top of rocky hill;

At 1859 vrs. pass 28 23 vrs. E. of the N. W. Cor. of Sur. No. 54 Block No. 5, H. &. T. C. Ry. Co.;

At 1900 vrs. set stone monument 4' x 1-1/2' x 4" marked "C. L. 3" set in mound of stone, from which

A mesquite 5" dia. brs. N. 2º E. 35-1/2 vrs.;

A windmill brs. N. 40-1/2 W.

STH MILE.

Thence South 3' East:

- At 1160 vrs. creek, course N. E.;
- At 1300 vrs. road, S. E. & N. W.;

At 1871 vrs. pass 16 vrs. E. of the N. W. Cor. of Sur. No. 51, Block 5,

5, H. & T. C. Ry. Co., a stone mound found and identified; At 1900 vrs. set stone monument 4' x 1-1/2' x 4" marked "C. L. 2" set

in mound of stone on the S. W. slope of a hill, from which A windmill brs. N. 75-1/4° West;

A hackberry mott on top of hill brs. S. 12-1/4° West.

9TH MILE.

Thence South 3' East:

At 300 vrs. road, draw, S. W.;

At 390 vrs. draw N. W.;

At 1888 vrs. fence E. & W. pass 8 vrs. E. of the N. W. Cor. of Sur. No. 36, Block No. 5, H. & T. C. Ry. Co., a stone mound found and identified

At 1900 vrs. set stone monument #" 3' x 1' x 4" marked " C. L. 1" set

in mound of stone on S. W. slope, from which

A hackberry 6" dia. brs. S. 5-1/2° East 132 vrs.

10TH MILE.

Thence South 3' East:

At 370 vrs. draw, S. E .;

At 1420 vrs. draw, East;

At 1900 vrs. the S. E. Cor. of Sur. No. 35, Block No. 5, H. & T. C. Ry. Co., a stone mound found and identified, set a stone monument 4-1/2' x 1-1/2' x 6" marked "S. E. Cor. S. Co." on N. W. face, "S. E. 35" on N. W. face, and "T. G. Co." on S. E. face, set in mound ofstone, from which

A mesquite 5" dia. brs. N. 64-1/4° W. 33-3/4 vrs.;

A mesquite 6" dia. brs. S. 5° E. 42-1/2 vrs., the same being the South S. E. Cor. of Sterling, and a Re-entering N. W. Cor. of Tom Green County.

> IST MILE West of the S. E. Cor. Sterling County. Thence South 88° 29' West over rocky prairie:

At 600 vrs. draw S. E. ;

At 1891 vrs. pass 64 vrs. S. of the N. W. Cor. of Sur. No.34, Block No. 5, H. & T. C. Ry. Co., the same being the N. E. Cor. of Sur. No. 81, Block No. 6, H. & T. C. Ry. Co., Cor. found and identified, Which is a mound of stone, from which

68

· 19.

2

A mesquite 3" dia. Brs. S. 46° 40' East;

At 1900 vrs. set a stone monument 4' x 1-1/2' x 4" in mound of stone marked "C. L. 1", from which

A mesquite 8" dia. brs. S. 56° East 60-3/4 vrs.; A mesquite 6" dia. brs. N. 62-3/3° East, 55-1/2 vrs.

2ND MILE.

Thence South 88° 29' West:

At 350 vrs. draw South;

At 1200 vrs. draw N. E.;

At 1500 vrs. top of a hill;

At 1900 vrs. draw South, true point of a mile in draw, at 1910 vrs. set a stone monument 30" x 16" x 4" marked "W. C. C. L. 2", from which A mesquite 8" dia. bts. S. 58-1/4° East, 45 vrs.;

A double mesquite brs. S. 38-1/2° West, 24 vrs.

3D MILE.

Thence 88° 29' West from true point of mile in draw over rocky prairie:

At 1 vr. pass 130 vrs. S.of the N. W. Cor. of Sur. No. 81, Block No. 6 H. & T. C. Ry. Co., a stone mound found and identified;

At 95 vrs. fence, N. & S.;

At 550 vrs. top of hill;

At 1165 vrs. draw S. W.;

At 1470 vrs. draw S. E.;

At 1480 vrs. draw S. E.;

At 1900 vrs. set a stone monument 40" x 20 x 4" marked "C. L. 3" in mound of stone, from which

A mesquite 6" dia. brs. S. 15-1/4° East 55 vrs.;

A mesquite 6" dia.brs. N. 11° East 69 vrs.

4TH MILE.

Thence South 88° 29' West:

At 22 vrs. fence N. &.S., from which the N. W. Cor. of Sur. No. 82,

Block 6, H. & T. C. Ry. Co. brs. N. 274 vrs., astone mound found and identified;

78

At 170 vrs. draw S. E.;

At 700 vrs. top of spur;

conter 58926

At 1450 vrs. Findlater & Richardson Ranch Road N. 20° E. & S. 20° West; At 1670 vrs. draw S. E.;

At 1900 vrs. a set stone monument in mound of stone marked "C. L. 4" on

N. E. slope of hill, from which A mesquite 8" dia. brs. N. 52-3/4⁰ East, 39 vrs.; A mesquite 8" dia. brs.N. 1-1/4⁰ East, 42 vrs.

5TH MILE.

Thence South 88° 29' West:

At 37 vrs. pass 304 vrs. S. of the N. W. Cor. of Sur. 83, Block 6, H. &

T. C. Ry. Co., a stone mound found and identified;

At 500 Wes. top of hill;

At 1200 vrs. road, S. E. & N. W.;

At 1315 vrs. draw South;

At 1900 vrs. set a stone monument in mound of stone on S. W. slope of hill, marked "C. L. 5" from which

A mesquite 6" dia. brs. N. 85° West, 23 vrs.;

A mesquite 5" dia. brs. \$. 49-1/4° West, 19 vrs.

6TH MILE.

Thence South 88° 29' West:

At 51 vrs. pas 334 vrs. S. of the N. W. Cor. of Sur. 84, Block 6, H. & T. C. Ry. Co., a stone mound found and identified;

At 195 vrs. fence N. & S.;

At 480 vrs. creek S. E.;.

At 1487 vrs. pass 93 vrs. N, of windmill;

At 1500 vrs. rocky creek, S. E.;

At 1880 vts. Stiles & San Angelo Road, S.E. & W. W.;

At 1900 vrs. set stone monument 30" x 18" x 4" in mound of stone in mesquite flat, marked "C. L. 6", from which

A mesquite 8" dia. brs. S. 56-1/4 E. 17 vrs.;

A mesquite 10" dia. Brs. N. 56-1/4 E. 24-1/2 vrs., the same being 1 vr. South of above named road.

Thence South 88° 29' West:

At 61 vrs. pass 399 vrs. S. 6f the N. W. Cor. of Sur. 85, Block 6, H. & T. C. Ry. Co., a stone mound found and identified;

At 1400 vrs. draw N.E.;

At 1900 vrs. set a stone monument 30" x 16" x 4" in mound of stone marked "C. L. 7" from which

A mesquite 8" dia. brs. N. 20-1/2 E. 38-1/2 vrs.;

A mesquite 6" dia. brs. N. 30-1/2° W. 51 vrs., this corner being on North slope of hill 30 vrs. S. of a draw, course East.

STH MILE.

Thence South 88° 29' West:

At 74 vrs. pass 462 vrs. South of the N. W. Cor. of Sur. 86, Block 6, H. &. T. C. Ry. Co., a stone mound found and identified;

At 500 vrs. top of hill;

At 1100 vrs. draw N. W.;

At 1625 vrs. draw N.;

At 1900 vrs. set stone monument 36" x 14" x 3" marked "C. L. 8" from which

A mesquite 10" dia. brs. N. 30° East 28 vrs.;

A mesquite 8" dia. brs. N. 68-1/2° West 24-1/2 vrs. this corner is 150 Vrs. E. of creek, and 30 East of road.

9TH MILE.

Thence South 88° 29' West:

At 87 vrs. pass 524 vrs. S. of the N. W. Cor. of Sur. 87, Block 6, H. & T. C. Ry. Co., a stone mound found and identified;

At 250 vrs. draw N. E.;

At 1250 vrs. draw S. E.;

At 1900 set stone monument 3' x 2' x 3" marked"C. L. 9" from which A mesquite 6" dia. brs. N. 89-1/2° W. 49-1/2 vrs.; A mesquite 8" dia. brs. N. 67-1/2° W. 6-1/2 vrs.

Thence South 88° 29' West:

At 97 vrs. pass 589 vrs. S. of the N. W. Cor. of Sur. 88, Block 6, H. & T. C. Ry. Co., and the N. E. Dor. of Sur. 41, Block 7, H. & T. C. Ry. Co., a stone mound found and identified, thence along top of rocky ridge;

At 1900 vrs. set stone monument 3' x l' x 6" marked "C. L. 10" in mound of stone, from which

A mesquite 5" dia. brs. S. 41-3/4° W. 52-1/4 vrs.; A mesquite 5" dia. brs. S. 71° W. 97 vrs.

11TH MILE.

Thence South 88° 29' West:

At 100-1/2 vrs. pass 1260 vrs. N. of S. W. Cor. of Sur. 41, Block 7, H. & T. C. Ry. Co., Cor. found and identified, a stone mound from which

A mesquite 6" dia. brs. S. 82-1/4° W. 70 vrs.; At 244 vrs. draw N.;

At 1800 vrs. fence N. & S.;

At 1900 vrs. set stone monument 4' x 2' x 10" in mound of stone on W. slope of hill, marked "C. L. 11", from which A mesquite 5" dia. brs. N. 73-1/4° W. 35-1/4 vrs.;

A double mesquite brs. N. 24-1/2° E. 32-1/2 vrs.

12TH MILE.

Thence South 88 29' West:

At 120 vrs. pass 1196 vrs. N. of the S. W. Cor. of Sur. 42, Block 7, H. & T. C. Ry. Co., a stone mound found and identified;

At 200 vrs. draw S.;

At 1900 vrs. set stone monument 3' x 2' x 4" in mound of stone marked "C. L. 12", from which

A mesquite 6" dia. brs. S. 74° E. 32-1/2 vrs.;

A mesquite 5" dia. brs. N. 55° W. 44 vrs., this **Dei**ner being on top of hill in mesquite timber.

Thence South 88° 29' West:

At 133 vrs. pass 1129 vrs. N. of the S. W. Cor. of Sur. 43, Block 7, H. & T. C. Ry. Co., a stone mound found and identified;

At 700 vrs. a draw, N.;

At 1900 set stone monument 36" x 30" x 3" in mound of stone on W. slope of hill, marked "C. L. 13" from which

A mesquite 4" dia. brs . S. $44-1/4^{\circ}$ E. 20 vrs.; A mesquite 5" dia. brs. N. $44-1/2^{\circ}$ W. 38 vrs.

14TH MILE.

Thence South 88° 29' West:

At 149-1/2 vrs. pass 1064 vrs. N. of the S. W. Cor. of Sur. 44, Block 7,

H. & T. C. Ry. Co., a stone mound found and identified;

At 700 vrs. a draw of Kioawa Creek, S. W.;

At 1900 set stone monument 40" x 18" x 3" in mound of stone marked & "C.

L. 14", from which

Chittim mott on top of hill bts. S. 43-3/4° West;

Hackberry mott on West slope of hill brs. N. 49° East, this Cor. being

on West slope of hill.

15TH MILE.

Thence South, 88° 29' West:

At 166-1/2 pass 998 vrs. N. of the S. W. Cor. of Sur. 45, Block 7, H. &

T. C. Ry. Co., a stone mound, from which

A mesquite # 4" dia. brs. N. 69-1/4° W. 47 vrs.;

A stone mound brs. N. 35 vrs., found and identified;

At 300 vrs. draw N. W.;

At 1300 vrs. Kioawa Creek, course S. W.;

At 1900 vrs. set stone monument 30" x 14" x 5" in mound of stone at East

foot of hill, marked "C. L. 15" from which A mesquite 3" dia. brs. N. $30-1/2^{\circ}$ W. 12-1/4 vrs.; A mesquite 4" dia. brs. N. $2-1/4^{\circ}$ W. 30-1/4 vrs.

101/2E

The Thence South 88° 29' West:

At 17 vrs. Big Lake & Sterling City Road, N. 20° East;

At 194-1/2 vrs. pass 926 vrs. N. of the S. W. Cor. of Sur. 46, Block # 7

H. & T. C. Ry. Co., a stone mound from which

A mesquite 4" dia. brs. N. 54-1/4° East & 4 vrs.;

A mesquite 4" dia. brs. S. 49-1/4° West 22 vrs., found and identified; At 1460 vrs. road, S. E. & N. W.;

At 1850 preek creek, S. E.;

At 1900 vrs. set a stone monument 30" x 18" x 3" in mound of stone in

open mesquite flat, marked "C. L. 16", from which

A china 8" dia. brs. S. 50° East 45 vrs.;

A mesquite 9" dia. brs. S. 2-1/2° W. 19 vrs.

17TH MILE.

Thence South 88° 29' West:

At 208 vrs. pass 857-1/2 vrs. N. of S. W. Cor. of Sur. 47, Block 7, H.

& T. C. Ry. Co., a stone mound found and identified;

At 850 vrs. draw N. E.;

At 1800 head of a draw, S. E.;

At 1900 set stone monument 36" x 18" x #" in mound of stone on rocky

point, marked "C. L. 17", from which A mesquite 3" dia. brs. S. 56-1/2° E. 20 vrs.; A mulberry 10" dia. brs. N. 73-3/4° W. 95 brs.

18TH MILE.

Thence South 88° 29' West:

At 222-1/2 vrs. pass 788-3/4 vrs. N. of the S. W. Cor. of Sur. 48, Block 7, H. & T. C. Ry. Co., a stone mound, from which

A mesquite 4" dia. brs. S. 22-1/2° W. 16-2/5 vrs.;

A mesquite 5" dia. brs. S. 17-3/4° East 73-4/5 vrs., found and identified; At 1100 vrs. draw S.;

At 1900 vrs. set stone monument 36" x 16" x 4" in mound of stone on West

118

slope of hill, marked "C. L. 18", from which

A mesquite 10" dda. brs. N. 60° E. 70 vrs.;

A double mesquite brs. S. 6-3/4° E. 35 vrs.

Thence South 88° 29' West:

At 240-1/2 vrs. pass 382 vrs. S. of the N. W. Cor. of Sur. 15, Block A, G. C. & S. F. Ry. Co., a stone mound, from which

The South end of a china mott brs. N. 20° E. found and identified; At 244 vrs. fence N. & S.;

At 1120 draw N.;

At 1900 set stone monuments 30" x 20" x 4" in mound of stone in open mesquite flat, marked "C. L. 19" from which

A mesquite 3" dia. brs. N. 23° W. 34 vrs.;

A mesquite 3" dia. brs. S. 88-1/2° W. 9-1/2 vrs.

20TH MILE.

Thence South 88° 29' West:

At 2 vrs. fence N. & S.;

At 356-3/4 vrs. pass 22 vrs. N. of the S. E. Cor. of W. P. Huff Sur. 43, a stone mound found and identified;

At 1900 vrs. set stone monument 24" x 12" x 6" in mound of stone in b open mesquite flat, marked "C. L. 20", from which A mesquite 6" dia. brs. N. 1° W. 35 vrs.; A mesquite 10" dia. brs. S. 88-1/4° W. 91 vrs.

21ST MILE.

Thence South 88° 29' West:

At 575 vrs. pass 1 vr. S. of the S. E. Cor. of M. R. Smith Sur. 44; At 1900 vrs. set stone monument 24" x 6" x 8" in mound of stone on high, rolling ridge in mesquite timber, marked "C. L. 21", from which

128

A mesquite 5" dia. brs. N. 55-1/3° W. 22 vrs.; A catclaw 6" dia. brs. N. 53-3/4° E. 61-1/2 vrs.

22ND MILE.

Thence South 88° 29' West:

At 821 vrs. pass 19 vrs. S. of the S. E. Cor. of Sur. 27, T. C. Ry. Co., a mound of stone, from which

A bunch of bushes on E. side of draw brs. N. 40-1/4° W., found and

identified;

At 1000 vrs. a draw N. W.;

At 1200 vrs. a draw N.;

At 1900 vrs. set stone monument 26" x 12" x 3" marked "C. L. 22", from which

A mesquite 5" dia. brs. S. 7-3/4° E. ## 62-3/4 vrs.;

A clump of mesquites brs. N. 41-3/4° E. 5 vrs.

23D MILE.

Thence South 88° 29' West:

At 839 vrs. pass 2027 vrs. S. of the N. W. Cor. of Sur. 27, T. C. Ry. Co.

a stone mound, from which

A mesquite 3" dia. brs. N. 24° W. 1 vr.;

A mesuite 4" dia. brs. S. 70° W. 5 vrs., found and identified;

At 1430 vrs. Middle Concho draw, S.;

At 1700 vrs. rocky ridge, N. & S.;

At 1900 vrs. set stone monument 26" x 8" x 6" in mound of stone marked

"C. L. 23" from which

A leaning mesquite 5" dia. brs. S. $40-1/4^{\circ}$ E. 9 vrs.; 5 hackberries brs. S. $65-3/4^{\circ}$ W. 80-1/2 vrs.

24TH MILE.

Thence South 88° 29' West:

At 750 vrs. creek, S. E.;

At 1369-1/2 vrs. intersect East Line of Reagan County, and West Line of Sterling and Tom Green Counties, at a point 984 vrs. South of the 6th mile stone from the N. E. Corner of Reagan County, the same being the 36th mile stone from the N. W. Cor. of Sterling County, said point being 412-1/4 vrs. W. of the N. W. Cor. of Sur. 29, T. C. Ry. Co., a stone mound, found and identified, set a stone monument 5-1/2' x 2-1/2' x 10" marked "S. W. Cor. S. Co., Apr. 15, 1907" on on North face, and "N. W. Cor. T. G. Co." on South face, set in

mound of stone on North slope of hill, from which

A mesquite 4" dia. brs. S. 55-1/2° East, 50 vrs.;

A mesquite 4" dia. brs. S. 46-3/4° West, 47-1/2 vrs., the same being the N. W. Cor. of Tom Greem County, and the S. W. Corner of Sterling

County.

The Corners called for and connected with, in H. & T. C. Blocks, No. 5, 6, & 7, are those located by S. Turner in 1886, for H. & T. C. Ry. Co.

counter 58934

148

THE STATE of TEXAS, # # COUNTY of TOM GREEN. #

WE, J. E. Beavers, Surveyor for Tom Green County, and W. F. Kellis, Surveyor for Sterling County, do hereby certify over our official signatures that the within and foregoing described Survey was actually made by us upon the ground in conformance with the statutes made and provided in such cases, and the act creating Sterling County, on the dates and with the chain carriers aforesaid, duly qualified, and that all the Corners, Monuments, Lines, Bearings and Boundaries are truly and correctly described and set forth in the foregoing plat and field notes.

> W. T. Tucker) (Chain Carriers. 0. Rutledge)

J. E. Blavert Surveyor for Jour Erun Co N. F. Rellis surveyor for Sterling Co.

The State of Texas, *

1.0

. . .

County of Sterling. * I, J.S.Cole County Clerk and Exofficio Clerk of the Commissioners Court of Sterling County, Texas, hereby certify that the above and foregoing is a true and correct copy of an order passed by the Commissioners Court of Sterling County, Texas, on May 17th, 1907, and also a true and correct copy of the Map and Field notes mentioned in said Order as the same appears of record in Book 1 pages 577 to 590, inclusive of the Minutes of said Court.

Witness my hand and seal of office this llth day of July, A.D. 1907.

and Experies Clerk Commissioners Court Sterling County, Texas.

A MAN of THE SOUTH LINE OF STERLING COUNTY Rega H. &. T. C. Ry. Co R ,35 W. B. Deansur 43-M3"NSTOR. 5 M.U"STOR. 5 200 18 2 13 Bl. Sterling G. ×46 112 48 W.P. Huff 20 30 18 75 M.R.Smith W.B. Bean F. Salinas R Tom S G reen ¥ 63

M. F. Rellis surveyor 126 for steeling county

P.

BL

G.C.&S.FRY

-1919-

S.

T. C. Ry. Co

Anta Motos

H. &. T. C. Ry. Co BL. 6. 7. County 43 42 42 45' THA 44 3 9- 88 8 87 10" 87 4 89. Inters B21/4 MA 74 5 (79 Count 4

